



OGDEN COMMUNITY SERVICES BLDG REMODEL CONSTRUCTION DOCUMENTS



OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden UT 84401
OGDEN CITY



DRAWING INDEX

DRAWING INDEX	
SHEET NUMBER	SHEET NAME
GENERAL	
G000	COVER SHEET
G001	DRAWING INDEX, SYMBOLS AND ABBREVIATIONS
G100	GENERAL NOTES
G120	CODE DATA
4	
ARCHITECTURAL	
AD101	DEMOLITION FLOOR PLAN
AE101	FLOOR PLAN & REFLECTED CEILING PLAN
AE102	INTERIOR ELEVATIONS
AE600	DOOR & WINDOW SCHEDULE & ELEVATIONS
AE841	INTERIOR DETAILS
5	
STRUCTURAL	
SE001	PLANS AND DETAILS
1	
MECHANICAL	
M000	General Notes & Legends
M201	Mechanical Plan
M501	Mechanical Details
3	
PLUMBING	
P201	Plumbing Plan
P000	Plumbing Notes & Legends
2	
ELECTRICAL	
ED101	LEVEL 1 - DEMOLITION PLAN
EG000	GENERAL NOTES AND SYMBOLS LISTS
EG002	ELECTRICAL DETAILS
EG003	ELECTRICAL SCHEDULES
EL101	LEVEL 1 - LIGHTING PLAN
EL201	LIGHTING PHOTOMETRY PLAN
EP101	LEVEL 1 - POWER AND SYSTEMS PLAN
7	



VICINITY MAP

Ogden Community Services

Write a description for your map.

DRAWING INDEX

Legend

1875 Monroe Blvd

HYDRANT

INCHES OR INCH

INFORMATION

INSULATION

INTERIOR

LAVATORY

LIGHT WEIGHT

MAINTENANCE

MANUFACTURER

MASONRY OPENING

MATERIAL

MAXIMUM

MECHANICAL

METAL

MINIMUM

MISCELLANEOUS

NOT IN CONTRACT

NOT TO SCALE

NUMBER

ON CENTER

OPPOSITE

OUTSIDE DIAMETER

OVERHEAD

OVERHEAD DOOR

OVERHEAD DOOR

OWNER FURNISHED CONTRACTOR

OWNER FURNISHED OWNER

PAINTED OR PAINT

PARTITION

PERPENDICULAR

PLATE

POUNDS PER CUBIC FOOT

POUNDS PER LINEAL FOOT

POUNDS PER SQUARE FOOT

POUNDS PER SQUARE INCH

RADIIUS

REFLECTED CEILING PLAN

REINFORCED

REQUIRED

ROOF DRAIN

ROOM

ROUGH OPENING

SCHEDULE

SHEET

SIMILAR

SOUND TRANSMISSION

SPECIFICATION

STANDARD

STRUCTURAL

SUSPENDED

THRU

TOP OF

TOP OF ASPHALT

TOP OF CURB

TOP OF FOOTING

TOP OF SLAB OR SIDEWALK

TOP OF WALL


UNLESS NOTED OTHERWISE

VENEEER

NOTE:
ABBREVIATIONS FOR FINISHED
MATERIALS ARE DESCRIBED IN
THE FINISH LEGEND.

DRAWING INDEX

GRID



GRID LINES

GRID

#

DETAIL SYMBOL
DETAIL NUMBER/
SHEET WHERE DETAIL IS DRAWN

#

BUILDING SECTION SYMBOL
SECTION REFERENCE/
SHEET WHERE SECTION IS DRAWN

#

WALL SECTION SYMBOL
SECTION REFERENCE/
SHEET WHERE SECTION IS DRAWN

#

EXTERIOR ELEVATION SYMBOL
ELEVATION IDENTIFICATION
SHEET WHERE ELEVATION IS DRAWN

#

INTERIOR ELEVATION SYMBOL
ELEVATION IDENTIFICATION
SHEET WHERE ELEVATION IS DRAWN

100A

ELEVATION CONTROL POINT
OR DATUM POINT

W1

DOOR TAG
DOOR NUMBER

NAME

WINDOW TAG
WINDOW OR STOREFRONT NUMBER

#

ROOM TAG
ROOM NAME
ROOM NUMBER

A

REVISION TAG

#

VIEW TITLE
VIEW NUMBER/
SHEET WHERE VIEW IS LOCATED
VIEW NAME/VIEW SCALE

CONCRETE MASONRY UNIT

FACE BRICK

CONCRETE (POURED IN PLACE)

GYPSUM BOARD OR SETTING BEDS

INSULATION (BATT & BLANKET)

INSULATION (RIGID/SEMI-RIGID)

PLYWOOD

CONTINUOUS ROUGH WOOD

BLOCKING, ROUGH WOOD

METAL (LARGE SCALE)

GRAVEL

EARTH

COMPACTED FILL

QUARRY/CERAMIC TILE

FIREPROOFING

WOOD

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.:

GSBS PROJECT NO.:

2023.04.00

ISSUED DATE:

07/21/2025

DRAWING INDEX, SYMBOLS
AND ABBREVIATIONS



GENERAL NOTES

1. ALL WORK SHALL CONFORM TO THE CONTRACT DOCUMENTS WHICH INCLUDE THE OWNER/CONTRACTOR AGREEMENT, THE DRAWINGS, AND ALL ADDENDA AND MODIFICATIONS ISSUED BY THE ARCHITECT.

2. THE CONTRACTOR SHALL REVIEW DOCUMENTS AND VERIFY DIMENSIONS AND FIELD CONDITIONS. ANY OMISSIONS OR DISCREPANCIES SHALL BE REPORTED IN WRITING TO THE ARCHITECT AS SOON AS POSSIBLE. REVIEW UNCONDITIONAL CONDITIONS OR CONDITIONS THAT VARY FROM THE CONTRACT DOCUMENTS WITH THE ARCHITECT PRIOR TO THE INSTALLATION OF NEW WORK.

3. IF DOCUMENTS ARE AT VARIANCE WITH ONE ANOTHER ON A PARTICULAR ITEM OR ITEMS, THE CONTRACTOR SHALL BASE THE PROPOSAL ON THE MOST STRINGENT OF THE CONDITIONS. ITEMS OR EQUIPMENT SPECIFIED UNDER ONE TRADE SHALL BE BINDING AS SPECIFIED UNDER ALL APPLICABLE TRADES.

4. THE CONTRACTOR SHALL INCLUDE IN BILL ALL COSTS FOR AND SHALL ARRANGE FOR HOSTING, CARTING, ELEVATOR SERVICE, STANDARDS AND OVERTIME SERVICES TO THE BUILDING MANAGEMENT AND OVERTIME CHARGES AND EXPENSES WHEN REQUIRED, DUE TO BUILDING MANAGEMENT REQUIREMENTS.

5. WHERE REQUIRED, THE CONTRACTOR SHALL FILE AND OBTAIN FOR THE BUILDING, DEPARTMENT AND OTHER AGENCY APPROVALS AND PERMITS, CONTROLLED INSPECTIONS, AND FINAL WRIT-EFFS FOR PROJECT COMPLETION. COPIES OF TRANSACTIONS TO BE FORWARDED TO THE ARCHITECT AND BUILDING MANAGEMENT PRIOR TO COMMENCING WORK.

6. THE OWNER SHALL PAY FEES FOR ANY OF THE ABOVE.

7. THE CONTRACTOR SHALL ARRANGE FOR INSPECTIONS NECESSARY TO OBTAIN A CERTIFICATE OF OCCUPANCY BY OFFICIALS AS DESIGNATED BY THE AUTHORITY HAVING JURISDICTION.

8. THE CONTRACTOR SHALL MAINTAIN FOR THE ENTIRE LENGTH OF CONTRACT EXITS, EXIT LIGHTING, FIRE PROTECTIVE DEVICES AND ALARMS TO CONFORM TO LOCAL BUILDING CODE REQUIREMENTS, IN OCCUPIED AREAS OF THE BUILDING.

9. WORK AND/OR CONSTRUCTION OPERATIONS SHALL NOT UNDERMINE THE STRUCTURAL INTEGRITY OF THE BUILDING.

10. THE CONTRACTOR SHALL VERIFY THAT DRAWINGS ARE THE LATEST ISSUE PRIOR TO COMMENCING CONSTRUCTION.

11. IN CASE OF CONFLICT BETWEEN ARCHITECT'S AND ENGINEER'S DRAWINGS IN LOCATION OF MATERIALS/EQUIPMENT, THE ARCHITECTURAL DRAWINGS SHALL GOVERN.

12. THE CONTRACTOR SHALL NOT PROGRESS WITH WORK WHICH REQUIRES ADDITIONAL COMPENSATION BEYOND THE CONTRACT AMOUNT WITHOUT WRITTEN AUTHORIZATION FROM THE OWNER. FAILURE TO OBTAIN SUCH AUTHORIZATION SHALL INVALIDATE A CLAIM FOR EXTRA COMPENSATION.

13. WORK SHALL BE PERFORMED DURING REGULAR BUSINESS HOURS WHENEVER POSSIBLE. WORK INVOLVING EXCESSIVE NOISE OR DUST, OR WORK WHICH WOULD OTHERWISE INTERFERE WITH THE WORK OF OTHERS, OR WORK WHICH COULD DAMAGE THE TENANT'S PROPERTY OR DAMAGE NON-REGULAR BUSINESS HOURS BASIS OR AS AGREED TO WITH OWNER OR TENANTS. THIS SHALL BE COORDINATED WITH BUILDING MANAGEMENT.

14. THE CONTRACTOR SHALL COORDINATE WORK, INCLUDING, BUT NOT LIMITED TO, SCHEDULING TIME AND LOCATIONS FOR DELIVERIES, BUILDING ACCESS, BUILDING FACILITIES AND USE AND CLEARANCE OF AVAILABLE ELEVATORS WITH BUILDING MANAGEMENT.

15. WORK AREAS SHALL REMAIN SECURE DURING CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE, WHERE NECESSARY, TEMPORARY, LOCKABLE DOORS TO PROVIDE THE TENANT CONSTANT ACCESS TO SPACES NOT UNDER CONSTRUCTION. CONTRACTOR SHALL PROVIDE TENANT WITH KEYS FOR TEMPORARY DOORS, IF REQUIRED.

16. THE CONTRACTOR SHALL PROVIDE A FULL-TIME SUPERINTENDENT OR REPRESENTATIVE AT THE JOB SITE DURING ALL WORK HOURS WHO SHALL SUPERVISE AND DIRECT THE WORK ACCORDING TO THE SPECIFIED QUALITY STANDARDS.

17. THE CONTRACTOR SHALL APPLY, INSTALL, CONNECT, ERECT, CLEAN AND/OR REPAIR MANUFACTURED ARTICLES, MATERIALS, AND/OR EQUIPMENT PER MANUFACTURER'S INSTRUCTIONS. IN CASE OF CONFLICT BETWEEN MANUFACTURER'S INSTRUCTIONS AND THE CONTRACT DOCUMENTS, THE CONTRACTOR SHALL OBTAIN WRITTEN CLARIFICATION FROM THE ARCHITECT BEFORE PROCEEDING.

18. THE CONTRACTOR IS RESPONSIBLE FOR CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES AND PROCEDURES AND FOR THE COORDINATION OF WORK AND FOR THE WORK PERFORMED BY THE SUBCONTRACTORS.

19. THE CONTRACTOR SHALL COORDINATE AND SCHEDULE WORK BY OTHERS, INCLUDING BUT NOT LIMITED TO, TELEPHONE, DATA, FURNISHED AND/OR INSTALLED OWNERS PROVIDED ITEMS. CONTRACTOR SHALL COORDINATE EXACT LOCATIONS AND SHALL DO THE CUTTING, FITTING, AND PATCHING THAT MAY BE REQUIRED TO MAKE THE PARTS OF THE WORK WHICH WILL RECEIVE THE WORK OF OTHERS COMPATIBLE, WITH WHAT IS SHOWN OR REASONABLY IMPLIED BY THE DRAWINGS.

20. BEFORE CUTTING EXAMINAR AREAS TO BE CUT, PROTECT EXISTING CONSTRUCTION DURING CUTTING AND PATCHING TO PREVENT DAMAGE. PROVIDE TEMPORARY SUPPORT DO NOT CUT AND PATCH STRUCTURAL ELEMENTS IN A WAY THAT COULD REDUCE THEIR LOAD CARRYING CAPACITY. DO NOT CUT AND PATCH IN A MANNER THAT COULD CAUSE IN VISUAL EVIDENCE OF CUTTING AND PATCHING. SALVAGE, CLEAN AND REINSTALL CUT AND PATCHED EXISTING BUILDING ELEMENTS TO BE REUSED IN THE NEW WORK, AS INDICATED ON THE DRAWINGS.

21. THE CONTRACTOR SHALL PROTECT THE BUILDING PREMISES AND OCCUPANTS ON THE PROJECT SITE FROM DAMAGE OR INJURY RESULTING FROM HIS OPERATIONS. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN NECESSARY COVERINGS, BOARDS, TEMPORARY PARTITIONS, AND DOORS AS REQUIRED TO PROTECT EXISTING WORK, MATERIALS, AND FINISHES TO REMAIN AT THE JOB SITE. THE CONTRACTOR SHALL NOT DAMAGE OR DESTROY EXISTING CONSTRUCTION, MATERIALS, EQUIPMENT AND REPAIRS OR REPLACEMENTS WITHOUT ADDITIONAL CHARGE TO THE PARTY AFFECTED.

22. SUBSTITUTIONS, REVISIONS, OR CHANGES MUST BE SUBMITTED TO ARCHITECT FOR REVIEW AND APPROVAL, IN CONFORMANCE WITH SPECIFIED PROCEDURES PRIOR TO FABRICATION OR INSTALLATION.

23. IMMEDIATELY PRIOR TO THE OWNER'S OCCUPANCY OF ANY PHASE, THE CONTRACTOR SHALL CLEAN SURFACES OF DUST, DEBRIS, LOOSE CONSTRUCTION MATERIAL, EQUIPMENT AND SHALL LEAVE FLOORS VACUUMED AND CLEAN. REMAINING CONSTRUCTION MATERIAL AND EQUIPMENT, IF ANY, SHALL BE MOVED AND TEMPORARILY SECURED IN AN AREA DIRECTED BY THE OWNER.

24. THE CONTRACTOR SHALL CLEAN WINDOWS AND WINDOW COVERINGS, AND SHALL VACUUM THE INSIDE OF CONVECTOR ENCLOSURES IMMEDIATELY PRIOR TO OWNER OCCUPANCY.

25. DO NOT SCALE DRAWINGS. CLARIFICATION OR INFORMATION REQUIRED BY THE CONTRACTOR WILL BE FURNISHED BY THE ARCHITECT UPON WRITTEN REQUEST FROM THE CONTRACTOR.

26. TYPICAL OR TYP SHALL MEAN THAT THE CONDITION IS REPRESENTATIVE FOR SIMILAR CONDITIONS THROUGHOUT, UNLESS OTHERWISE NOTED. DETAILS ARE USUALLY KEYED AND NOTED TYP WHEN THEY FIRST OCCUR.

27. SIMILAR OR SIM' MEANS COMPARABLE CHARACTERISTICS FOR THE CONDITIONS NOTED. VERIFY DIMENSIONS AND ORIENTATION ON PLANS AND ELEVATIONS.

28. DIMENSIONS AND NOTES FOR A GIVEN CONDITION ARE TYPICAL FOR SIMILAR CONDITIONS UNLESS OTHERWISE NOTED.

29. IN THE CASE OF CONFLICT BETWEEN NOTES ON DRAWINGS, INCLUDING ALL NOTES ON THIS SHEET, THE MOST STRINGENT REQUIREMENTS SHALL GOVERN. REQUEST CLARIFICATION FROM THE ARCHITECT IN ALL SUCH CASES.

30. CONTRACTOR SHALL COORDINATE WITH THE OWNERS TELEPHONE/DATA CONTRACTOR FOR THEIR WORK.

31. GENERAL CONTRACTOR SHALL THOROUGHLY INVESTIGATE EXISTING CONDITIONS AND SHALL COORDINATE ALL WORK WITH OWNER, INCLUDING ABATEMENT OF HAZARDOUS MATERIALS.

32. IF LEVELS ABOVE AND BELOW THE PROJECT AREA WILL BE CONTINUOUSLY OCCUPIED DURING CONSTRUCTION, CARE SHOULD BE TAKEN TO AVOID UNDUE DISTURBANCE TO TENANTS.

33. REFRIGERATOR, MICROWAVES, AND VENDING MACHINES ARE TO BE TENANT PROVIDED, CONTRACTOR INSTALLED.

CONSTRUCTION NOTES

1. REVIEW ALL CONTRACT NOTES AND NOTES BEFORE COMMENCING WORK.

2. DIMENSIONS MARKED "CLEAR" SHALL BE MAINTAINED AND SHALL ALLOW FOR THICKNESS OF FINISHES INCLUDING CARPET, CERAMIC TILE, VCT, ETC. CONTRACTOR SHALL NOT ADJUST DIMENSIONS WITHOUT WRITTEN INSTRUCTION FROM THE ARCHITECT.

3. DIMENSIONS MARKED "CLEAR" ARE TO BE WITHIN 1/16" ALONG FULL HEIGHT AND FULL WIDTH OF WALLS TO FINISHED FACE OF GYPSUM BOARD.

4. CONTRACTOR SHALL PREPARE LAYOUT PARTITIONS FOR ARCHITECT TO REVIEW FOR DESIGN INTENT. DO NOT PROGRESS WITH INSTALLATION OF STUDS WITHOUT THIS REVIEW APPROVAL. CONTRACTOR SHALL COORDINATE AND VERIFY CONDITIONS TO ENSURE PROPER FIT. REVIEW FOR DESIGN INTENT DOES NOT RELEASE CONTRACTOR FROM RESPONSIBILITY TO MAINTAIN CRITICAL DIMENSIONS AND CLEARANCES.

5. NEW GYPSUM BOARD CONSTRUCTION ADJOINING EXISTING CONSTRUCTION IN THE SAME PLANE SHALL BE FLUSH WITH NO VISIBLE JOINTS, UNLESS OTHERWISE NOTED.

6. EXPOSED GYPSUM BOARD EDGES SHALL HAVE A 1/2" TRIM. PROVIDE CLEAT READS ALONG FULL LENGTH OF EXPOSED EDGES. BEAD ALONG EXPOSED EDGES OF GYPSUM BOARD. UNLESS OTHERWISE NOTED, TAPE, SPACKLE AND SAND JOINTS. PARTITIONS SHALL HAVE A SMOOTH FINISHED CONDITION READY FOR PAINT AND FINISH MATERIAL APPLICATION, UNLESS NOTED OTHERWISE.

7. PENETRATIONS IN GYPSUM BOARD CONSTRUCTION ABOVE FINISHED CEILING SHALL BE EFFECTIVELY SEALED TO PREVENT SOUND LEAKAGE AT ACOUSTICAL PARTITIONS AND AT DEMISING PARTITIONS, UNLESS OTHERWISE NOTED.

8. INSTALL GLASS USING FGMA STANDARDS FOR TYPE OF SYSTEM. REMOVE ALL NON-PERMANENT LABELS.

9. CONTRACTOR TO INSTALL ALL CEILING MATERIALS FINISHES AND FIXTURES IN ACCORDANCE WITH SPECIFICATIONS BY THE CURRENT CODE FOR THE JURISDICTION.

10. LIFE SAFETY SYSTEMS CONSISTING OF BUT NOT LIMITED TO FIRE SPRINKLERS, ALARM HORNS AND STROBES, ETC., TO BE DRAWN AND ENGINEERED BY OTHERS ACCORDING TO CODE AND BUILDING STANDARD.

11. PROVIDE DRAWINGS FOR REVIEW BY ARCHITECT'S OFFICE REGARDING THERMOSTAT/FIRE ALARM EQUIPMENT LOCATIONS

12. FIELD VERIFY ALL CONDITIONS TO DETERMINE EXACT DIMENSIONS PRIOR TO FABRICATION.

13. PROVIDE BLOCKING AT ALL WALLS TO RECEIVE MILLWORK. THE G.C. AND MILLWORK CONTRACTOR TO COORDINATE REQUIRED LOCATION FOR CONCEALED BLOCKING TO ADEQUATELY SUPPORT THE MILLWORK. ALL ATTACHMENT HARDWARE SHALL BE CONCEALED FROM VIEW.

14. COORDINATE ELECTRICAL CONTRACTOR ACCESS SERVICE WAYS WITH C.C. PRIOR TO FABRICATION. PROVIDE FIELD CUTOUTS AS REQUIRED AT INTERIOR OF MILLWORK FOR WIREWAYS.

FINISH NOTES

1. ALL WORK THAT REQUIRES OPEN FLAME OR PRODUCES ANY SPARK SUCH AS SOLDERING OF PIPE JOINTS, WELDING, CUTTING OF METAL STUDS WILL REQUIRE A WORK PERMIT PRIOR TO COMMENCING WITH ANY SUCH WORK. CONTRACTOR SHALL CONTACT THE BUILDING ENGINEER FOR A "HOT WORK" PERMIT.

2. SWEEPING AND DUST. CONTRACTOR SHALL SEAL OFF THE RETURN AIR DUCT IN THE SPACE PRIOR TO ANY SWEEPING OR CREATION OF DUST. ALL SWEEPING SHALL BE DONE USING A SWEEPING COMPOUND WITH SUFFICIENT AMOUNT TO PREVENT ANY DUST FROM FORMING.

3. CONTRACTOR SHALL ENSURE THAT ALL SMOKE DETECTION DEVICES ARE COVERED PRIOR TO AND DURING CONSTRUCTION.

4. THERE MUST BE A 1/2" DEFLECTION DETAIL AT THE TOP OF ALL WALLS THAT CONNECT TO THE STRUCTURE ABOVE.

5. ALL FLOOR PENETRATIONS MUST BE COORDINATED WITH BUILDING MANAGEMENT, THE TENANT LOCATED ON FLOOR BELOW, CORE DRILLED AND PERFORMED AFTER HOURS.

6. LOCK CYLINDERS SHALL BE SCHLAGE IC 6 PIN "C" CORES KEYED TO THE BUILDING MASTER KEY SCHEDULE. ALL KEYING TO BE DONE BY GLEN'S KEYS.

7. ALL INSULATION BATTES EXPOSED IN THE PLENUM CEILING MUST BE FSK-25 WRAPPED (JOHNS-MANVILLE COMFORT THERM OR APPROVED EQUAL) AND CUT TO ALLOW ALL CEILING TILE TO BE MOVED FOR ACCESS TO PLENUM.

8. IN "WET" AREAS THAT CONTAIN SINKS, FLOOR SINKS, ICE MACHINES, SHOWERS/RESTROOMS, ETC. THE BASE BUILDING CONCRETE SLAB MUST BE SEALED WALL TO WALL WITH A WATERPROOFING MEMBRANE PRIOR TO THE INSTALLATION OF FINISH FLOORING.

9. ALL DOOR FINISHES AND HARDWARE THAT ADJOIN THE BUILDING COMMON AREA MUST MATCH THE BASE BUILDING STANDARD FINISH ON THE COMMON AREA SIDE.

10. ALL FLOOR LEVELING AND FLOOR PREPARATION NEEDS TO BE INCLUDED WITHIN THE CONTRACTOR'S SCOPE OF WORK AND INCLUDED WITHIN THE BID.

BUILDING OWNER NOTES

REVISIONS:

1. REVIEW ALL CONTRACT NOTES AND NOTES BEFORE COMMENCING WORK.

2. CONTRACTOR SHALL PROPERLY PREPARE SURFACES PER FINISH MATERIAL MANUFACTURER'S SPECIFICATIONS PRIOR TO APPLICATION OF FINISH.

3. ENSURE SURFACES TO RECEIVE FINISHES ARE CLEAN, TRUE AND FREE OF IRRREGULARITIES - DO NOT PROCEED WITH WORK UNTIL UNSATISFACTORY CONDITIONS HAVE BEEN CORRECTED. STARTING WORK SHALL INDICATE APPLICATORS ACCEPTANCE OF SUBSTRATE.

4. REPAIR AND PREPARE EXISTING SURFACES AS REQUIRED FOR APPLICATION OF SCHEDULED FINISHES.

5. PREPARE FLOOR AREAS AS REQUIRED TO RECEIVE FLOOR FINISHES INCLUDING LEVELING AS REQUIRED TO ACHIEVE A SMOOTH FLOOR.

6. FOR CARPET PREPARATION CLEAN FLOORS OF DUST, DIRT, SOLVENTS, OIL, GREASE, PAINT, PLASTER, AND SUBSTANCES DETERMINED TO IMPAIR PERFORMANCE OF ADHESIVE AND CARPET AS RECOMMENDED BY MANUFACTURER. ALLOW FLOORS TO THOROUGHLY DRY.

7. COMPLY WITH MANUFACTURER'S PRINTED INSTRUCTIONS IN THE INSTALLATION OF THE CARPET.

8. LAY CARPET IN THE SAME DIRECTION, UNLESS SPECIFICALLY SHOWN OTHERWISE. MAINTAIN UNIFORMITY OF DIRECTION AND LAY CARPET WITH A MINIMUM OF SEAMS, NO CROSS JOINTS PERMITTED. AVOID SEAMS AT CONSPICUOUS LOCATIONS NEAR DOORS AND CORNERS.

9. NEATLY TRIM CARPET EDGES FOR TIGHT FIT ALONG WALLS. CUT AND FIT EVENLY AROUND PROJECTIONS AND INTRUSSIONS AND REVEALS. FIT CLOSELY AND EVENLY TO DOORWAYS AND PUCKERS.

10. INSTALL GLASS USING FGMA STANDARDS FOR TYPE OF SYSTEM. REMOVE ALL NON-PERMANENT LABELS.

11. REMOVE OR PROVIDE SURFACE APPLIED PROTECTION TO HARDWARE, HARDWARE ACCESSORIES, MACHINED SURFACES, PLATE, LIGHT FIXTURES, AND SIMILAR ITEMS IN PLACES WHICH ARE NOT TO BE FINISH-PAINTED. FOLLOWING COMPLETION AND AFTER SURFACES ARE COMPLETELY DRY, REINSTALL REMOVED ITEMS AND/OR REMOVE PROTECTION FROM ITEMS.

12. FIELD VERIFY ALL CONDITIONS TO DETERMINE EXACT DIMENSIONS PRIOR TO FABRICATION.

13. PROVIDE BLOCKING AT ALL WALLS TO RECEIVE MILLWORK. THE G.C. AND MILLWORK CONTRACTOR TO COORDINATE REQUIRED LOCATION FOR CONCEALED BLOCKING TO ADEQUATELY SUPPORT THE MILLWORK. ALL ATTACHMENT HARDWARE SHALL BE CONCEALED FROM VIEW.

14. COORDINATE ELECTRICAL CONTRACTOR ACCESS SERVICE WAYS WITH C.C. PRIOR TO FABRICATION. PROVIDE FIELD CUTOUTS AS REQUIRED AT INTERIOR OF MILLWORK FOR WIREWAYS.

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden, UT 84401

OGDEN CITY

133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.:


GSBS PROJECT NO.:

2023.04.00

ISSUED DATE:


07/21/2025

GENERAL NOTES

REVISIONS:
[REVISIONS]

CODE PLAN LEGEND	
EXIT (0.15 ft) XXX OCC X-X R X-X P	LOCATION (EXIT WIDTH FACTOR) GOVERNING FLOOR OCCUPANT NUMBER REQUIRED EXIT WIDTH PROVIDED EXIT WIDTH
XX	EXIT ACCESS TRAVEL DISTANCE
[Blank]	OCCUPANCY IS TYPE B UNLESS NOTED OTHERWISE

CODE REVIEW CRITERIA	
OCCUPANCY GROUPS	B - BUSINESS
TYPE OF CONSTRUCTION	TYPE V (ASSUMED)
FIRE SPRINKLERS	NO
NUMBER OF STORIES	1
EXISTING BUILDING SQ. FT.	(B) 4,298 SF (EXISTING BUILDING)
EXISTING BLDG. OCCUPANT LOAD:	4,298 / 150 = 29 OCCUPANTS (EXISTING)
PROJECT WORK AREA OCCUPANT LOAD:	2,583 / 150 = 18 OCCUPANTS
APPLICABLE CODES	- Effective 7/1/2024
15A-2-103. Specific editions adopted of construction code of a nationally recognized code authority.	
1. Subject to the other provisions of this part, the following construction codes are incorporated by reference, and together with the amendments specified in Chapter 3, Statewide Amendments Incorporated as Part of State Construction Code, and Chapter 4, Local Amendments Incorporated as Part of State Construction Code, are the construction standards to be applied to building construction, alteration, remodeling, and repair, and in the regulation of building construction, alteration, remodeling, and repair in the state:	
a. the 2021 edition of the International Building Code, including Appendices C and J, issued by the International Code Council;	
b. the 2021 edition of the International Residential Code, issued by the International Code Council;	
c. Appendix AQ of the 2021 edition of the International Residential Code, issued by the International Code Council;	
d. the 2021 edition of the International Plumbing Code, issued by the International Code Council;	
e. the 2021 edition of the International Mechanical Code, issued by the International Code Council;	
f. the 2021 edition of the International Fuel Gas Code, issued by the International Code Council;	
g. the 2020 edition of the National Electrical Code, issued by the National Fire Protection Association;	
h. the 2021 edition of the International Energy Conservation Code, issued by the International Code Council;	
i. the 2021 edition of the International Existing Building Code, issued by the International Code Council.	
2009 ADA ACCESSIBILITY GUIDELINES - ICC/ANSI A117.1	
SECTION 504 OF THE REHABILITATION ACT OF 1973	
2019 STATE CONSTRUCTION AND FIRE CODES ACT, AMENDED	



NOTE:
THE EXISTING ROOF STRUCTURE IS TO REMAIN. NO STRUCTURAL UPDATES TO THE ROOF STRUCTURE IS ANTICIPATED OR REQUIRED AT THIS TIME.

CONSTRUCTION DOCUMENTS

OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY



133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.:
GSBS PROJECT NO.: 2023.04.00
ISSUED DATE: 07/21/2025

CODE DATA



DEMOLITION LEGEND	
=====	EXISTING BUILDING ELEMENTS TO BE REMOVED
=====	EXISTING BUILDING ELEMENTS TO REMAIN
=====	SHADED AREAS NOT IN SCOPE OF WORK
DEFINITIONS	
A. REMOVE: DETACH ITEMS FROM EXISTING CONSTRUCTION AND DISPOSE OF THEM OFF-SITE UNLESS INSTRUCTED TO BE SALVAGED OR REINSTALLED.	
B. REPAIR: TO PREVENT DAMAGE, REMOVE ITEMS FROM EXISTING CONSTRUCTION, IN A MANNER TO PREVENT DAMAGE, AND STORE.	
C. REMOVE AND REINSTALL: DETACH ITEMS FROM EXISTING CONSTRUCTION, IN A MANNER TO PREVENT DAMAGE, PREPARE FOR REUSE, AND REINSTALL WHERE INDICATED.	
D. EXISTING TO REMAIN: LEAVE EXISTING ITEMS THAT ARE NOT TO BE REMOVED AND THAT ARE NOT OTHERWISE INDICATED TO BE SALVAGED OR REINSTALLED.	
E. DISMANTLE: TO REMOVE BY DISASSEMBLING, OR DETACHING, AN ITEM FROM A SUPPORT, AND USE CERTAIN METHODS AND EQUIPMENT TO PREVENT DAMAGE TO THE ITEM AND SURFACES; DISPOSING OF ITEMS UNLESS INDICATED TO BE SALVAGED OR REINSTALLED.	
DEMOLITION NOTES	
1. THE CONTRACTOR SHALL MAINTAIN THE EXISTING STRUCTURAL AND FIREPROOFING INTEGRITY OF THE ENTIRE BUILDING, EXCEPT WHERE OTHERWISE NOTED.	
2. SEE ENGINEERING DRAWINGS AND SPECIFICATIONS FOR THE REMOVAL OF SPECIFIC STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE ALARM SYSTEMS.	
3. REMOVE ALL EXISTING EQUIPMENT, DEVICES, AND MATERIALS OF ALL FOREIGN MATERIAL. REPLACE EQUIPMENT OR DEVICES WHICH ARE DEFECTIVE OR DAMAGED DURING RELOCATION.	
4. EXISTING SECURITY CAMERAS TO REMAIN THROUGHOUT CONSTRUCTION - CONTRACTOR TO VERIFY EXISTING DATA/POWER ROUTING & MAINTAIN UNINTERRUPTED.	
5. WHEREVER MECHANICAL, ELECTRICAL, AND PLUMBING DEVICES ARE REMOVED, ALL PIPING AND/OR CONDUIT, AND ALL CABLES AND WIRES SHALL BE PAPPED OFF BELOW THE FLOOR, CEILING, OR WALLS, OR ABOVE THE CEILINGS EXCEPT WHERE OTHERWISE NOTED. MECHANICAL/ELECTRICAL CONTRACTOR TO REMOVE ALL UNUSED WIRING TO PANEL BOXES. PATCH AND REPAIR FINISHES TO MATCH SURROUNDING FINISHES. COVER PLATES OVER EXISTING BOXES ARE NOT ACCEPTABLE, UNLESS OTHERWISE NOTED.	
6. REMOVE EXISTING WALL AND EXISTING WINDOW SYSTEM AS REQUIRED.	
7. REMOVE EXISTING DOOR & FRAME.	
8. REMOVE EXISTING STAIRWAY.	
9. REMOVE WALL BASE IN AREAS WHERE FLOORING IS BEING REMOVED.	
10. FLOORS AND WALLS: WHERE WALLS OR PARTITIONS THAT ARE REMOVED EXTEND ONE FINISHED AREA INTO ANOTHER, PATCH AND REPAIR FLOOR AND WALL SURFACES IN THE OPEN AREA TO PROVIDE AN EVEN SURFACE OF UNIFORM FINISH, COLOR, TEXTURE, AND APPEARANCE.	
11. EXISTING MILLWORK TO BE REMOVED. EXISTING COUNTERTOP GATE AND WINDOWS TO BE REMOVED IN ENTIRETY.	
NOTE: NOT ALL NOTE NUMBERS MAY BE USED ON THIS SHEET	



DEMOLITION FLOOR PLAN - LEVEL 1

AD101 1/8" = 1'-0"

0' 4' 8' 12' 16' 24'

GRAPHIC SCALE



CONSTRUCTION DOCUMENTS

OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY

133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.:

GSBS PROJECT NO.:

ISSUED DATE:

07/21/2025

DEMOLITION FLOOR PLAN



METAL STUD DEFLECTION CHART

16" STUD SPACING (1/360, 5psf)
3 5/8" STUD (1 5/8" FLANGE)
33 mils 15'-4" High (Max.)
54 mils 17'-10" High (Max.)
6" STUD (1 5/8" FLANGE)
33 mils 22'-8" High (Max.)
43 mils 24'-9" High (Max.)
12" STUD SPACING (1/360, 5psf)
8" STUD (2 1/2" FLANGE)
43 mils 37'-5" High (Max.)
54 mils 40'-3" High (Max.)
68 mils 43'-3" High (Max.)
97 mils 43'-9" High (Max.)

WALL TYPES NOTES

1. UNLESS NOTED OTHERWISE, DIMENSIONS LOCATING WALLS INDICATE: CENTERLINE OF STUD AT METAL STUD WALLS, FACE OF STUD AT WOOD STUD WALLS, CENTERLINE OF FACE OF STUD AT CONCRETE WALLS.
2. UNLESS NOTED OTHERWISE, SPECIFIED WALL TYPE TO CONTINUE AT DOOR AND WINDOW OPENINGS (TOP AND BOTTOM).
3. IN ADDITION TO THE REQUIREMENTS OF DIVISION 01 OF THE SPECIFICATION, PROVIDE WALL TYPE #38 IF NO OTHER WALL TYPE HAS BEEN INDICATED.
4. CLEARANCE DIMENSION TO FINISHED SURFACE INDICATED, INCLUSIVE OF ALL MATERIALS UTILIZED IN THE RELATED ASSEMBLY.
5. FOR WALL TYPES WITH AN 'H' DESIGNATION, PROVIDE MANUFACTURER'S RECOMMENDED STRAPPING AT NO LESS THAN 4'-0" O.C. VERTICALLY, WHEN THE WALL IS NOT DIRECTLY ATTACHED TO A SUPPORTING WALL SURFACE.
6. WHERE METAL AND/OR WOOD STUDS ARE PROVIDED AS FURRING, INSTALL ALL CONCEALED ELEMENTS IN THE METAL AND/OR WOOD FRAMED ASSEMBLY.
7. PROVIDE FIRE RETARDANT TREATED PLYWOOD BACKING ON ALL WALLS INDICATED TO RECEIVE WALL MOUNTED EQUIPMENT IN ELECTRICAL, DATA, IDP/MOP ROOMS.
8. UNLESS NOTED OTHERWISE, DOOR JAMBES WITHIN METAL AND/OR WOOD STUD WALLS SHALL BE LOCATED 4" CLEAR FROM ADJACENT WALL.
9. PROVIDE SUITABLE BLOCKING IN METAL AND/OR WOOD FRAMED WALLS AND CEILINGS AS REQUIRED FOR INSTALLATION OF MECHANICAL, PLUMBING AND ELECTRICAL EQUIPMENT AND SPECIALTIES.
10. WHERE METAL AND/OR WOOD STUDS ARE INSTALLED DIRECTLY AGAINST EXTERIOR CONCRETE WALLS, EXTERIOR CONCRETE WALLS OR DISSIMILAR MATERIALS AT EXTERIOR WALLS, INSTALL ISOLATION STRIP BETWEEN STUDS AND EXTERIOR WALL.
11. PROVIDE GLASS-MAT WATER RESISTANT GYPSUM BOARD AT ALL LOCATIONS INDICATED TO RECEIVE TILE. INSTALL WITH 1/4 INCH GAP WHERE PANELS ABUT OTHER CONSTRUCTION OR PENETRATIONS. WHERE TILE IS LAYING PANELS ABUT OTHER TYPES OF PANELS IN SAME PLANE, SHIM SURFACES TO PRODUCE A UNIFORM PLANE ACROSS PANEL SURFACE.
12. UNLESS NOTED OTHERWISE, PROVIDE LEVEL 4 FINISH AT GYPSUM BOARD PANEL SURFACES THAT WILL BE EXPOSED TO VIEW.

WALL TYPES SCHEDULE


vv	STC	UL#	DESCRIPTION	RATING	PLAN
NON-RATED METAL STUD WALLS					
D38i	45		3 5/8" METAL STUDS @ 16" O.C. W/ 5/8" GYPSUM BOARD, EACH SIDE. EXIST GYPSUM BOARD, 1/2" FIBERGLASS SOUND ATTENUATION BLANKET		
D38i	55		SEE COMMENT # 1: 3 5/8" METAL STUDS @ 16" O.C. W/ (2) LAYERS 5/8" GYPSUM BOARD, EACH SIDE AND (1) LAYER 3 1/2" FIBERGLASS SOUND ATTENUATION BLANKET		
D38i	35		3 5/8" METAL STUDS @ 16" O.C. W/ 5/8" GYPSUM BOARD OVER 8'-0" HIGH BALLISTIC PANEL ONE SIDE AND (1) LAYER 5/8" GYPSUM BOARD, EACH SIDE, FILL CAVITY WITH 3 1/2" FIBERGLASS SOUND ATTENUATION BLANKET		
D6Ci	55		6" METAL STUDS @ 16" O.C. W/ (2) LAYERS 5/8" GYPSUM BOARD, EACH SIDE AND (1) LAYER 3 1/2" FIBERGLASS SOUND ATTENUATION BLANKET		
METAL STUD FURRING					
H38			3 5/8" METAL STUDS @ 16" O.C. W/ 5/8" GYPSUM BOARD, ONE SIDE ONLY. EXTEND GYPSUM BOARD, 1/2" FIBERGLASS SOUND ATTENUATION BLANKET		

NOTE:
ALL AREAS WITH EXISTING CARPET TO RECEIVE NEW CARPET I.U.O.

WHICH TERMINATES AT 8'-0" AFF. REFER TO DETAIL 1/AE102.

ROOM FINISH SCHEDULE


Level	Number	Name	Wall Finish	Base Finish	Floor Finish
LEVEL 1	100	EXISTING VESTIBULE	P1	WD	CP1
LEVEL 1	101	EXISTING RECEPTION	P1	WD	CP1
LEVEL 1	102	CEMETERY RECEPTION	P1	WD	CP1
LEVEL 1	103	CEMETERY OFFICE	P1	WD	CP1
LEVEL 1	104	BREAK ROOM	P1	WD	LV1
LEVEL 1	105	NEW OFFICE	P1	WD	CP1
LEVEL 1	106	NEW OFFICE	P1	WD	CP1
LEVEL 1	107	EXISTING OFFICE	P1	WD	CP1
LEVEL 1	108	EXISTING PARKS OFFICE	P1	EX	CP1
LEVEL 1	109	EXISTING DIRECTOR OFFICE	P1	EX	CP1
LEVEL 1	110	EXISTING RECREATION OFFICE	P1	EX	CP1
LEVEL 1	111	EXISTING SPORTS	P1	EX	EX
LEVEL 1	112	EXISTING OFFICE	P1	EX	CP1
LEVEL 1	113	EXISTING STAIRWAY	P1	EX	EX
LEVEL 1	114	NEW CONFERENCE ROOM	P1	EX	CP1
LEVEL 1	115	EXISTING MEN	EX	EX	EX
LEVEL 1	116	EXISTING WOMEN	EX	EX	EX
LEVEL 1	117	EXISTING CLERICAL	P1	WD	CP1
LEVEL 1	118	CORRIDOR	P1	WD	CP1



REFLECTED CEILING PLAN - LEVEL ONE

AE101 1/4" = 1'-0"

0' 2' 4' 6' 8' 12' GRAPHIC SCALE

NOTE - THIS SHEET IS INTENDED
TO BE VIEWED IN COLOR

2 ENLARGED FLOOR AND WALL TYPES PLAN

AE101 1/4" = 1'-0"

FLOOR PLAN

AE101 1/8" = 1'-0"

0' 4' 8' 12' 16' 24' GRAPHIC SCALE

CONSTRUCTION DOCUMENTS
OGDEN COMMUNITY SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden, UT 84401

OGDEN CITY


133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.: GSBS PROJECT NO.: 2023.04.00




ISSUED DATE: 07/21/2025

FLOOR PLAN & REFLECTED
CEILING PLAN


AE101 REV



GLAZING LEGEND		
SC1	LEVEL 3 SECURITY GLAZING	
SC2	GLAZING TO MATCH EXISTING BUILDING GLAZING	
SC3	EXISTING GLAZING TO REMAIN	




3 CEMETERY OFFICE ELEVATION 1
AE102/ 1/2" = 1'-0"
GRAPHIC SCALE



CONSTRUCTION DOCUMENTS
OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden UT 84401
OGDEN CITY


133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.: GSBS PROJECT NO.: 2023.04.00
ISSUED DATE: 07/21/2025
INTERIOR ELEVATIONS






DOOR SCHEDULE												
	DOOR				FRAME		DETAILS			POWERED	DOOR NUMBER	
	PANELS	WIDTH	HEIGHT	TYPE	HEAD HEIGHT	TYPE	MATERIAL/ FINISH	DOOR HEAD	DOOR JAMB	DOOR THRESHOLD		
D101	SNGL	3'-0"	7'-0"	D2	WD / STN	2"	F1	HM / PNT			CARD READER (BY OWNER); BALLISTIC RESISTANT DOOR	D101
D102B	SNGL	3'-0"	7'-0"	D2	WD / STN	2"	F1	HM / PNT			CARD READER (BY OWNER); BALLISTIC RESISTANT DOOR	D102B
D103B	SNGL	3'-0"	7'-0"	D1	WD / STN	2"	F1	WD / STN			MATCH EXISTING DOORS & OFFICE HARDWARE	D103B
D105	SNGL	2'-6"	7'-0"	D1	WD / STN	2"	F1	WD / STN			MATCH EXISTING DOORS & OFFICE HARDWARE	D105
SF-1	SNGL	3'-0"	7'-0"	D4	ALUM / CLR	SEE ELEV	ALUM / CLR				HARDWARE BY MFR.	SF-1

GLAZING LEGEND

SG1 - LEVEL 3 SECURITY GLAZING
SG2 - GLAZING TO MATCH EXISTING BUILDING GLAZING
SG3 - EXISTING GLAZING TO REMAIN



DOOR TYPES

NEW WINDOW HEAD DETAIL
AE601 / 1 1/2" = 1'-0"NEW WINDOW SILL DETAIL
AE601 / 1 1/2" = 1'-0"

STOREFRONT TYPES

WINDOW TYPES

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY

133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.:



GSBS PROJECT NO.:

ISSUED DATE:


2023.04.00

07/21/2025


DOOR & WINDOW
SCHEDULE & ELEVATIONS




8 BALLISTIC PANEL INSTALLATION @ J-BOX
AE841 3" = 1'-0"




4 BALLISTIC COUNTER NATURAL VOICE BAFFLE
AE841 6" = 1'-0"




6 TRANSACTION COUNTER SECTION
AE841 1 1/2" = 1'-0"




5 BALLISTIC PANEL INSTALLATION DETAIL
AE841 1" = 1'-0"



3 BALLISTIC NATURAL VOICE BAFFLE SYSTEM
AE841 6" = 1'-0"



2 BALLISTIC PANEL WINDOW JAMB @ COUNTER
AE841 6" = 1'-0"



1 BALLISTIC PANEL DOOR JAMB
AE841 6" = 1'-0"

CONSTRUCTION DOCUMENTS
OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden, UT 84401
OGDEN CITY

133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.:
GSBS PROJECT NO.: 2023.04.00
ISSUED DATE: 07/21/2025

INTERIOR DETAILS

REVISIONS:	
A	

BASIS OF DESIGN

1. Governing Building Code: International Building Code 2021, International Existing Building Code 2021 - Alteration Level 2
2. Risk Category: II
3. Roof Snow Load (Not concurrent with Roof Snow Load): 20 psf
4. Roof Snow Load: A. Ground Snow Load: $P_g = 38$ psf
B. Full Roof Snow Load: $P_f = 7$ psf
C. Wind Exposure Factor: $C_w = 1.0$
D. Thermal Factor: $C_t = 1.0$
E. Snow Load Importance Factor: $I_s = 1.0$
5. Wind Load: A. Basic Wind Speed (3 Second Gust): 105 mph
B. Wind Importance Factor: 1.00
C. Wind Exposure: C
D. Internal Pressurization Coefficient: 0.18
E. Seismic Design Category: D
F. Seismic Design Category: D
G. Lateral Force Resisting System(s): Intermediate Masonry Shear Walls per IBC 304.3.1 and TMS 7-16
H. Seismic Design Category: D
I. Seismic Design Category: D
J. System Overstrength Factor: $O_s = 3.5$
K. System Deflection Amplification Factor: $C_d = 2.25$
L. Design Base Shear: $V = 0.75 C_f W = 0.235 W$, where W is structural weight
H. Analysis Procedure: Equivalent Lateral Force

STRUCTURAL STEEL

1. Codes and Standards: Fabrication, Erection and Quality Control of structural steel shall comply with the latest edition of the following:
A. American Institute of Steel Construction (AISC) 360, "Specification for Structural Steel Buildings," with "Commentary".
B. AISC 360-16, "Specification for Structural Steel Buildings".
C. AISC 303 Code of Standard Practice" covering sections 3.4 and 4.4.1.
D. AISC Specification for Structural Joints Using High Strength Bolts"
E. American Welding Society (AWS) Structural Welding Codes D1.1, D1.3, D1.4, and D1.8, as modified by the "Steel Construction Manual".
2. Materials:
A. Wide Flange Sections: ASTM A992 (50 kips)
Notch-toughness requirements apply for Group 3, 4, and 5 shapes with flange thickness greater than 1 1/2" and plate 2" and thicker which are a part of the Seismic Load Resisting System (SLRS). Minimum Charpy V-Notch requirements are 20 ft-lbs at 70°F.
B. Structural Shapes: ASTM A36
C. Hollow Structural Shapes: ASTM A500 Grade C (40 kips)
1. Rectangular: ASTM A500 Grade C (40 kips)
2. Circular: ASTM A500 Grade C (40 kips)
D. Other Structural Shapes (M, C, etc.), Threaded Rod: ASTM A38
E. Bolted Connections: ASTM F313 Grade A25 with ASTM A563 heavy hex nuts and ASTM F436 washers.
F. Welded Filler Metal:
1. Structural Welded Filler Metal: AWS A5.1 low-hydrogen only
Low-hydrogen restrictions do not apply when welding steel sheets in accordance with AWS D1.3, including attaching these steels to structural members.
2. Gas-shielded Metal-Cored Arc Welding: AWS A5.18
3. Flux-Cored Arc Welding: AWS A5.20
EWT-4 or EWT-11 electrodes are not permitted.
4. Interning of welds made from self-shielded welding electrodes with welds made by other processes is not allowed in seismic critical welds, unless tested in accordance with D1.8, annex B. The Field Erection section of the specification provides for verifying that intermixing of self-shielded and other electrodes does not occur. If intermixing does occur, the welding process is qualified by testing.
5. Where demand critical welds are required, provide filler metal meeting the following minimum mechanical properties: 30ksi yield strength, 70ksi tensile strength, 22% elongation, Charpy V-notch toughness of 20ft-lbs at 0°F and 40ft-lbs at 70°F.
G. Deformed Bar Anchors (DBA): ASTM A493
H. Deformed Bar Anchors (HSA): ASTM A493
I. Non-Shrink Grout: ASTM C110/Grade B
Non-shrink grout shall be prepackaged, non-metallic and non-gaseous.
Furnish certified independent test data for Structural Grout.
Refer to "Structural Grout" by ACI 230.

J. Refer to architectural drawings for structural steel preprinting or galvanized or externally exposed steel requirements.

K. All steel connectors and embeds exposed to weather shall be galvanized, unless otherwise noted.

3. Structural Details:
A. Field welding: Field welding shall be performed in the shop or the field. Designations of field welds on the Contract Documents are shown where it is anticipated field welds may be required, and are shown only for the purpose of assisting the Contractor in the bidding process. The Contractor shall coordinate the welding sequence between sub-contractors, and any costs associated with variations in the welding sequence are outside the scope of the Design Engineer, and are the responsibility of the Contractor. Field welding is to be minimized where possible. Contractor is to verify that the sequencing of welding does not affect all safety requirements, and the requirements of the Construction Documents and their referenced codes. Welding in the 'X' position of wide flange members is prohibited unless noted otherwise.
B. Bolts and Fasteners:
1. Ordinary steel-to-steel connection, simple span framing, and beam/ledger-to-bearing plates are the standard connection used throughout the building.
a. Use A325N bolts or tension-controlled bolts.
b. Tighten these fasteners to a "snug tight" condition.
c. Where a steel-to-steel connection is not provided, provide a framed connection per AISC for one half the total uniform load capacity of the beam for the span length specified.
2. Pretensioned fasteners are shown on the structural design drawings. They join steel-to-steel connections, unless noted otherwise:
a. Use A325N or A325X bolts or tension-controlled bolts.
b. Tighten these fasteners as required by AISC "Specification for Structural Joints Using ASTM A325 or A490 Bolts."
3. Fasteners and washers shall not be reused. Scrap, rusty, or water-contaminated bolts assemblies.
C. All welds not noted to otherwise shall be minimum 1/4" fillet welds.
D. All structural steel members shall be considered as an unrestrained fire-resistance-rated assembly.

WOOD

1. Materials (Dry service conditions assume: Max moisture content of 15% for Sawn Lumber and Connections; 16% for all others)
A. Dimension Lumber and Lumber (Sawn Lumber) shall be USDOC PS20
2. Visually graded dimension lumber shall be Douglas Fir-Larch #2 or better.
A. For 900, $E = 1.610^6$, $F_{p,0} = 625$, $F_v = 180$, $F_{p,1} = 575$, $G = 0.5$.
3. Visually graded lumber (5' x 7' and larger) shall be Douglas Fir-Larch #1 or better.
A. Beam Strength: $E = 1.610^6$, $F_{p,0} = 625$, $F_v = 170$, $F_{p,1} = 575$, $G = 0.5$.
4. Machine stress rated (MSR) lumber shall be 1650# E or better. For 1650, $E = 1.610^6$, $F_{p,0} = 1000$, $F_v = 825$, $G = 0.5$.
5. Approved potted lumber may be interchanged with solid sawn members of the same species and grade.

B. Nails:
1. All Nails shall conform to the requirements specified in ASTM F167, "Standard Specification of Driven Fasteners: Nails, Spikes and Staples."
2. All nails shall be common nails with the following properties:
Nails with $\frac{1}{4}$ " shank diameter: $\frac{1}{4}$ " min. Penetration into Support
6d: $0.113^{\prime\prime}$ - $1.25^{\prime\prime}$
8d: $0.131^{\prime\prime}$ - $1.50^{\prime\prime}$
10d: $0.148^{\prime\prime}$ - $1.63^{\prime\prime}$
12d: $0.165^{\prime\prime}$ - $1.75^{\prime\prime}$
16d: $0.182^{\prime\prime}$ - $1.75^{\prime\prime}$
Nails with properties less than those listed above shall not be used without prior written approval from Dunn Associates, Inc. Hy-Tek nails may be substituted for common nails per ESR-2640.
3. Nails with $\frac{1}{4}$ " shank diameter in casing heads are not permitted. Nails with Round (full), Offset, Oval, Capped or Notched heads are acceptable.
4. Deformed shank nails shall have either a helical (screw) or an annular (ring) shank.

C. Connection Hardware:
1. All connection hardware shown shall be supplied by Simpson Strong-Tie Incorporated, unless noted otherwise. Install all hardware per the manufacturer's guidelines, filling all available holes with nails.
2. Connection hardware of equal design properties, including Mek-USP Structural Connectors or other manufacturers may be substituted, with written approval from Dunn Associates, Inc.

2. Per ESR-34.3, all mechanical, structural, and drainage systems shall accommodate for the effects of wood shrinkage, approximately 1/4" per foot per 1% moisture loss. Vertical expansion joints on vertical pipes, or other industry standards, 1/4" per foot accounts for 5% (allowing 1/4" x 1/4" 5 plates is one plate, two top plates and two base plates).
All fasteners shall be hot-dipped galvanized or hot-dipped zinc-coated galvanized or stainless steel.

A. All wood in contact with concrete, masonry or soil shall be preservative-treated or reinforced.

5. Design values adjusted for fire-treated lumber using Pyroguard (ESR-7791). Substitutions eligible by approval.


6. Glue-laminated (GL) framing and carpentry shall be connected as per THE MINIMUM NAILING SCHEDULE, unless noted otherwise.

7. A bearing wall shall be required to have a header. See section A-A for details.


8. Provide either an additional joist within 2' of centerline of parallel partitions, or provide 2x4 flat blocking at 24"oc between joists to support partitions.

9. Solid blocking at eaves may be omitted where required for ventilation (1 block in 5), unless noted otherwise.

10. Holes or penetrations through bearing walls shall be limited to the clear space between studs. Holes in shear wall sheathing shall be limited to 6" diameter (max), spaced at a minimum of 3 diameters on center. The accumulated length of openings in a shear wall shall not exceed 20% of the wall length, unless noted otherwise.




1 FLOOR PLAN - LEVEL 1
NORTH
SE001 SCALE: 1/8" = 1'-0"




2 ROOF FRAMING PLAN
NORTH
SE001 SCALE: 1/8" = 1'-0"

MINIMUM NAILING SCHEDULE	
CONNECTION	NAILING
BRDG TO JST, TOE NAIL EA END	(2) 8d
ROD TO JST, TOE NAIL OR 8d	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
STUD TO TOP OR BOTTOM PLATE, END NAIL	(2) 16d OR (3) 3" x 0.131
STUD TO STUD, FACE NAIL	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
TOP PL, TOE NAIL, TOE NAIL	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
BLK STWN TO TOP PL, RAFTERS TO TOP PL, TOE NAIL	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
RIM JST TO TOP PL, TOE NAIL	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
TOP PL, LAPS AT WALL INTERSECTION, FACE NAIL	(2) 16d OR (3) 3" x 0.131 ALONG EA EDGE
CONT. HEADER, TWO PIECES	(2) 16d OR (3) 3" x 0.131 ALONG EA EDGE
OR 16d BOX AT 1'-0" ALONG EA EDGE	(2) 16d OR (3) 3" x 0.131
CEILING JST TO PL, TOE NAIL	(3) 8d
CONT. HEADER TO STUD, FACE NAIL	(4) 8d
CEILING JST TO STUD, PARTITIONS, FACE NAIL	(3) 16d OR (4) 3" x 0.131
RAFTER TO PL, TOE NAIL	(3) 8d
1" BRACE TO STUD AND PL, FACE NAIL	(2) 8d
STUD TO STUD AT WALL CORNER	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
BUTT-UP GROUD AND BM	(2) 16d OR (3) 3" x 0.131 AT 1'-0"oc
AND STAGGERED, (3) 3" x 0.131 AT ENDS AND EA SPLICE	(2) 16d OR (3) 3" x 0.131 AT ENDS AND EA SPLICE
COLLAR TIE TO RAFTER, FACE NAIL	(3) 10d
ROOF RAFTER TO ROOF BM OR HIP TOE NAIL	(3) 10d
END NAIL	(3) 16d OR (4) 3" x 0.131
JST TO BAND JST, END NAIL	(3) 16d OR (4) 3" x 0.131
LEADER STRIP, FACE NAIL AT EA JOIST	(3) 16d OR (4) 3" x 0.131
"PYWOOD" LEADER BOARD:	(3) 16d OR (4) 3" x 0.131
SUPER ROOF FRAMING SHEATHING (TO FRAMING)	(2) 16d OR (4) 3" x 0.131
1/2" AND LESS	8d
1/2" AND 1-1/4"	8d OR 10d
1-1/4" AND 1-1/2"	10d
COMBINATION SUB FLOOR - UNDERLAYMENT (TO FRAMING)	(2) 8d
3/4" AND LESS	8d
1-1/4" AND 1-1/2"	8d OR 10d
1-1/2" AND 1-1/4"	10d
NAILS SPACED AT 6 INCHES ON CENTER AT EDGES, 12 INCHES AT INTERMEDIATE SUPPORTS, EXCEPT 6 INCHES AT ALL SPANS WHERE SPANS ARE 48 INCHES OR MORE. FOR NAILING OF DIAPHRAGMS AND SHEAR WALLS, REFER TO THE APPROPRIATE SCHEDULE.	


NOTES:
1. ALL NAILS ARE COMMON NAILS, UNO
2. EXCERPT FROM BC TABLE 2304.10.1 ADD'L NAILING OPTIONS NOT SHOWN MAY BE USED, EXCLUDING STAPLES.
3. NAILING REQUIREMENTS HERE DO NOT REPLACE HARDWARE ON THE PLANS OR DETAILS.



4 TYPICAL WOOD HEADER DETAIL
SE001 NO SCALE



5 STEEL COLUMN AT NEW WINDOW DETAIL
SE001 NO SCALE





6 STEEL COLUMN SUPPORT AT ROOF
SE001 NO SCALE

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 MONROE BLVD, OGDEN UT 84401

OGDEN CITY



OWNER PROJECT NO.: 240268
DUNN PROJECT NO.: 07/21/2025
ISSUED DATE: 07/21/2025

PLANS AND DETAILS

WWW.DUNN-SE.COM
PH: 801-373-3877

REV SE001

OGDEN CITY PUBLIC WORKS

BALLISTIC RETROFIT

OGDEN, UTAH

REVISIONS:



MECHANICAL & ELECTRICAL
CONSULTING ENGINEERS, LLC.
1040 N 2200 WEST | SALT LAKE CITY, UT
T: 801.359.3158 | www.pve-ut.com

PROJECT MECHANICAL GENERAL NOTES

1. ALL MECHANICAL SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH THE CURRENT ADOPTED EDITION OF THE BUILDING CODES, FIRE CODES, MECHANICAL CODES AND PLUMBING CODES.

2. DRAWINGS AND SPECIFICATIONS ARE COMPLIMENTARY. THE MOST STRINGENT WILL WHATEVER IS CALLED FOR IN EITHER IS BINDING AS THOUGH CALLED FOR IN BOTH.

3. THE EQUIPMENT SPECIFIED ON THE DRAWINGS HAVE BEEN SELECTED AS THE BASIS OF DESIGN. THE USE OF REVIEWED OR APPROVED EQUALS SHALL BE COORDINATED BY THE CONTRACTOR FOR GENERAL CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND GENERAL COMPLIANCE WITH THE INFORMATION GIVEN IN THE CONTRACT DOCUMENTS. CONTRACTOR IS RESPONSIBLE FOR SPACE REQUIREMENTS, EQUIPMENT DIMENSIONS, AND PERFORMANCE WHICH SHALL BE CONFIRMED AND CORRELATED AT THE JOB SITE. FABRICATION PROCESSES AND TECHNIQUES OF CONSTRUCTION COORDINATION OF HIS WORK WITH THAT OF ALL OTHER TRADES AND THE SATISFACTORY PERFORMANCE OF HIS WORK.

4. DRAWINGS ARE DIAGRAMMATIC AND SHOW THE GENERAL DESIGN INTENT, ARRANGEMENT AND GENERAL EXTENT OF SYSTEMS. DO NOT SCALE DRAWINGS NOR USE AS SHOP DRAWINGS. NEW MECHANICAL EQUIPMENT, DUCTWORK AND PIPING ARE SHOWN AT APPROXIMATE LOCATIONS. THIS CONTRACTOR SHALL FIELD MEASURE/VERIFY ALL MECHANICAL/PLUMBING ITEMS PRIOR TO STARTING NEW WORK AND MAKE ADJUSTMENTS AS REQUIRED TO AVOID CONFLICTS WITHIN THE AVAILABLE SPACE. REVIEW THE GENERAL NOTES, SPECIFICATIONS AND PLANS FOR ADDITIONAL REQUIREMENTS THAT MAY NOT BE SPECIFICALLY CALLED OUT IN THIS PORTION OF THE CONSTRUCTION DOCUMENTS. NOTIFY THE ARCHITECT OF ANY CONFLICTS OR DISCREPANCIES PRIOR TO SUBMISSION OF BID. ANY MODIFICATIONS REQUIRED DUE TO LACK OF COORDINATION WILL BE THE RESPONSIBILITY OF THE CONTRACTOR.

5. VERIFY THAT EQUIPMENT LOCATIONS MEET MANUFACTURER'S RECOMMENDATIONS REGARDING SERVICE CLEARANCE AND PROPER AIRFLOW. FOR ALL EQUIPMENT, WHERE ALTERNATIVE ROUTING, OFFSETS, AND TRANSITIONS ARE REQUIRED FOR FIELD COORDINATION OF ALL OTHER TRADES, THIS CONTRACTOR SHALL FIELD COORDINATE WITH ALL OTHER TRADES, AND SHALL MAKE CHANGES WITHOUT ADDITIONAL COSTS.

6. PROVIDE TEMPORARY BARRIERS TO CONTAIN DUST AND DEBRIS RESULTING FROM THE PERFORMANCE OF THE WORK TO THE AREA WHERE WORK IS BEING PERFORMED.

7. THIS CONTRACTOR SHALL PROVIDE SUBMITTALS ON ITEMS LISTED IN EQUIPMENT SCHEDULE & SPECIFICATIONS TO THE ENGINEER FOR REVIEW PRIOR TO THE ORDER, PURCHASE OR INSTALLATION.

8. M.C & PC. TO PROVIDE A CONSTRUCTION RECORD SET OF "AS-BUILT" DOCUMENTS TO THE ARCHITECT/ENGINEER REFLECTING ANY VARIANCES OF INSTALLED PIPING LOCATIONS OR EQUIPMENT CONTRARY TO THE CONSTRUCTION DOCUMENTS WITHIN 60 DAYS OF SUBSTANTIAL COMPLETION.

9. ALL FLOW RATES, PRESSURES, AND TEMPERATURES MUST BE BALANCED TO THE VALUES INDICATED ON THE FLOOR PLANS. PROVIDE A FINAL BALANCE REPORT FOR THE TESTING AND ADJUSTING OF ALL NEW SYSTEMS SHALL BE COMPLETED PRIOR TO THE FINAL APPROVAL BY THE FIELD INSPECTOR. THIS REPORT SHALL BE SIGNED BY THE INDIVIDUAL RESPONSIBLE FOR PERFORMING THESE SERVICES. T.A.B. CONTRACTOR BY GENERAL CONTRACTOR.

10. EACH TRADE IS RESPONSIBLE FOR THE INSTALLATION OF LISTED FIREPROOFING SYSTEMS AT PENETRATION OF RATED ASSEMBLIES. ACCESSORIES & FIXTURES (i.e. CLEAUNOTS, DRYER BOXES, WASHING MACHINE BOXES) INSTALLED IN FIRE RATED WALLS SHALL UTILIZE A TESTED UL FIRE STOP ASSEMBLY.

11. HOUSEKEEPING PADS FOR ALL EQUIPMENT ARE PROVIDED AND INSTALLED BY GENERAL CONTRACTOR. COORDINATE LOCATION WITH MECHANICAL CONTRACTOR. PROVIDE HOUSE-KEEPING PADS FOR ALL MECHANICAL EQUIPMENT INSTALLED AT GRADE & OR FINISHED SLAB.

12. CONTRACTORS TO COMPLY WITH MANUFACTURER'S INSTRUCTIONS, INCLUDING EACH STEP IN SEQUENCE. WHEN MANUFACTURER'S INSTRUCTIONS CONFLICT WITH CONTRACT DOCUMENTS, REQUEST CLARIFICATION FORM ARCHITECT/ENGINEER BEFORE PROCEEDING WITH ANY WORK.

13. PLUMBING CONTRACTOR MUST PROVIDE AND INSTALL ALL ACCESS DOORS FOR PLUMBING COMPONENTS. PROVIDE ACCESS PANELS FOR EQUIPMENT INSTALLED ABOVE HARD LID CEILINGS. COORDINATE ACCESS PANEL LOCATIONS AND SIZES WITH G.C. ACCESS PANELS SHALL BE LARGE ENOUGH TO REMOVE EQUIPMENT WITHOUT DAMAGING PERMANENT CONSTRUCTION. INSTALL VALVES AND APPURTENANCES IN ACCESSIBLE LOCATION WITHIN 24" OF ACCESS DOORS OR ACCESSIBLE CEILING TILES.

14. CONTRACTOR TO PROVIDE SEISMIC ENGINEERED DRAWINGS AND DETAILS FOR ALL MECHANICAL AND PLUMBING ITEMS REQUIRING SEISMIC/WIND LOAD BRACING. THE DRAWINGS SHALL BE STAMPED BY A QUALIFIED SEISMIC ENGINEER. THE DRAWINGS SHALL INCLUDE DESIGN FOR SEISMIC/WIND LOAD BRACING. THE DRAWINGS SHALL BE SUBMITTED TO THE MECHANICAL CONTRACTOR AND TO THE CITY AS A DEFERRED SUBMITTAL. ANY INFORMATION ON THESE DRAWINGS RELATED TO SEISMIC IN THIS DRAWING SET ARE MINIMUM SUGGESTIONS ONLY. SEISMIC DRAWINGS SHALL TAKE PRECEDENCE.

15. COORDINATE ALL FIRE SPRINKLER HEADS AND AIR DEVICE LOCATIONS WITH REFLECTED CEILING PLANS AND ELECTRICAL DRAWINGS.

16. FIRE SPRINKLER CONTRACTOR SHALL ADD AND/OR RELOCATE SPRINKLER HEADS PER REFLECTED CEILING PLAN AND THE CURRENT ADOPTED EDITION OF NFPA AND BUILDING CODE.

17. DUCTWORK SHALL BE INSULATED PER IEC 403.11.1:

- A. SUPPLY AND RETURN DUCTWORK OUTSIDE OF BUILDING SHALL BE INSULATED WITH MIN. R-12
- B. SUPPLY AND RETURN DUCTWORK INSIDE OF BUILDING (EXCLUDING BUT OUTSIDE ENVELOPE) INCLUDING SHAFTS, VENTILATED ATTICS AND VENTILATED CRAWL SPACES SHALL BE INSULATED WITH MIN. R-6
- C. SUPPLY AND RETURN DUCTWORK INSIDE OF BUILDING IS NOT REQUIRED, WITH THE FOLLOWING EXCEPTIONS

a. ALL RECTANGULAR SUPPLY AND RETURN DUCTWORK WILL RECEIVE 1" DUCT LINER FOR SOUND ABATEMENT PURPOSES.

18. ALL DUCTWORK IS TO BE COMPLETELY SEALED USING DESIGN POLYMERS DP1010 DUCT SEALER OR APPROVED EQUAL.

19. THIS CONTRACTOR SHALL FIELD VERIFY ALL MECHANICAL ITEMS PRIOR TO STARTING NEW WORK. ADDITIONAL COST WILL NOT BE ALLOWED FOR CONTRACTOR'S FAILURE TO BECOME FAMILIAR WITH EXISTING SITE CONDITIONS.

20. THIS CONTRACTOR SHALL USE SMACNA DUCT CONSTRUCTION STANDARDS FOR SHEET METAL DUCTS. ALL HIGH PRESSURE DUCTWORK SHALL BE CONSTRUCTED FOR 2" W.C. STATIC PRESSURE, SEAL CLASS "A". ALL OTHER DUCTWORK, UNLESS OTHERWISE NOTED, SHALL BE CONSTRUCTED FOR 2" W.C. STATIC PRESSURE, SEAL CLASS "B".

21. ALL DIFFUSERS MUST BE BALANCED TO THE VALUES INDICATED ON THE FLOOR PLANS. PROVIDE BALANCE REPORT TO ENGINEER PRIOR TO PROJECT CLOSEOUT.

22. DUCT DIMENSIONS SHOWN ARE INSIDE CLEAR DIMENSIONS.

23. MECHANICAL CONTRACTOR IS TO COORDINATE WITH ELECTRICAL ON SIZE/QUANTITY OF MOTORIZED DAMPERS. I.E. FIRE/SMOKE DAMPERS, FIRE DAMPERS, MOTORIZE DAMPERS, ETC...

24. EACH TRADE IS RESPONSIBLE FOR THEIR OWN FIRE CAULKING.

25. MECHANICAL CONTRACTOR MUST PROVIDE AND INSTALL ALL ACCESS DOORS FOR POU'S, VALVES, FLOW METERS, ETC. COORDINATE LOCATION WITH GENERAL CONTRACTOR. PROVIDE ACCESS PANELS FOR EQUIPMENT INSTALLED ABOVE HARD LID CEILINGS. COORDINATE ACCESS PANEL LOCATIONS AND SIZES WITH EQUIPMENT AND CEILINGS. ACCESS PANELS SHALL BE LARGE ENOUGH TO REMOVE EQUIPMENT WITHOUT DAMAGING PERMANENT CONSTRUCTION.

26. HOUSEKEEPING PADS FOR ALL EQUIPMENT ARE PROVIDED AND INSTALLED BY GENERAL CONTRACTOR. COORDINATE LOCATION WITH MECHANICAL CONTRACTOR.

27. ALL TAKE-OFFS THROUGHOUT THE ENTIRE BUILDING SHALL BE HIGH EFFICIENCY TAKE-OFFS (HETS).

28. ALL RETURN AIR GRILLES SHALL HAVE SOUND BOOTS W/ LINED INSULATION. INSULATION IS TO BE PAINTED FLAT BLACK.

29. VFD'S ARE TO BE PROVIDED BY MECHANICAL AND WIRED AND INSTALLED BY ELECTRICAL CONTRACTOR.

30. ALL GAS METER REGULATORS ARE TO BE VENTED TO THE OUTSIDE OF THE BUILDING BY THE MECHANICAL CONTRACTOR OR PROVIDE / INSTALL VENTLESS REGULATORS IF ALLOWED BY THE LOCAL JURISDICTION. VENT PIPING FOR REGULATORS ARE NOT shown on the plans FOR CLARITY.

31. ALL FIRE DAMPERS SHOWN ON PLANS SHALL COMPLY WITH THE REQUIREMENTS OF UL 555. ALL SMOKE DAMPERS SHOWN ON PLANS SHALL COMPLY WITH UL 555S. ALL COMBINATION FIRE / SMOKE DAMPERS SHOWN ON PLANS ARE TO COMPLY WITH BOTH UL 555 AND UL 555S. FOR ALL FIRE DAMPERS CONTRACTOR IS TO PROVIDE / INSTALL "NCA MODEL FD" (OR EQUAL), TO MEET STANDARD UL 555 RATING. FOR ALL SMOKE DAMPERS AND COMBINATION FIRE SMOKE DAMPERS CONTRACTOR IS TO PROVIDE / INSTALL "NCA MODEL FSD-3V-211" (OR EQUAL), TO MEET STANDARD UL 555 AND UL 555S RATINGS.

32. THE MECHANICAL CONTRACTOR IS TO HAVE THE MANUFACTURER'S INSTALLATION INSTRUCTIONS FOR EACH TYPE OF FIRE DAMPER, SMOKE DAMPER, AND COMBINE FIRE / SMOKE DAMPERS ON THE JOB SITE AT TIME OF INSPECTIONS.

33. ALL DUCTWORK IS TO BE PROVIDED / INSTALLED AS HIGH UP AS POSSIBLE. ALL DUCTWORK MUST BE INSTALLED NO LOWER THAN 12' FROM WHERE IT IS BEING SUPPORTED OR SEISMIC BRACING WILL BE REQUIRED. IF DUCTWORK IS INSTALLED BELOW 12' FROM WHERE IT IS SUPPORTED, IT IS THE MECHANICAL CONTRACTOR'S RESPONSIBILITY TO HAVE SEISMIC SUPPORTS ENGINEERED FOR THE JOB BY A LICENSED ENGINEER.

34. ALL DUCT ELBOWS ARE TO BE PROVIDED / INSTALLED WITH RADIUS ELBOWS. ANY ALTERATIONS OR CHANGES IN DUCTWORK FROM WHAT IS SHOWN ON THE PLANS MUST BE PRE-APPROVED BY THE ENGINEER IN WRITING PRIOR TO ORDERING, FABRICATION, OR INSTALLATION.

35. MECHANICAL CONTRACTOR IS RESPONSIBLE FOR PROVIDING, INSTALLING, AND FILLING OUT GREEN GAS COMPLIANCE STICKERS FOR ALL GAS FIRED APPLIANCES. CONTRACTOR IS TO INSTALL ONE STICKER PER EVERY GAS FIRED APPLIANCE.

36. ALL T-STATS MUST BE MOUNTED AT 48" A.F.F. TO THE TOP OF THE STAT. ALL THERMOSTAT LOCATIONS ON THE PLANS SHALL COORDINATE WITH FURNITURE PLANS AND VERIFIED WITH OWNER PRIOR TO ROUGH-IN. T-STAT SHALL BE 7 DAY PROGRAMMABLE.

37. ALL EXHAUST AIR DUCTS ARE TO TERMINATE A MINIMUM OF 3' FROM ANY BUILDING OPENINGS AND 10' FROM ALL MECHANICAL AIR INTAKES.

38. ALL GRILLES, REGISTERS AND DIFFUSERS ARE TO BE PAINTED TO MATCH ADJACENT SURFACES BY THE GENERAL CONTRACTOR. FINAL COLOR TO BE DETERMINED BY ARCHITECT. ALL GRILLES ARE TO COME PRIMED FROM THE FACTORY AND FINAL PAINTING TO BE DONE IN FIELD BY G.C. GRILLES ARE TO BE PAINTED PRIOR TO FINAL INSTALLATION.

39. ALL EXTERIOR WALL VENTS, GRILLES, OR PIPING IS TO BE SELECTED OR PAINTED BY THE GENERAL CONTRACTOR TO MATCH THE ADJACENT SURFACE. SEE ARCHITECTURAL ELEVATIONS FOR EXACT EXTERIOR VENT LOCATIONS.

40. CONTRACTORS TO COMPLY WITH MANUFACTURER'S INSTRUCTIONS, INCLUDING EACH STEP IN SEQUENCE. WHEN MANUFACTURER'S INSTRUCTIONS CONFLICT WITH CONTRACT DOCUMENTS, REQUEST CLARIFICATION FORM ARCHITECT/ENGINEER BEFORE PROCEEDING WITH ANY WORK. IF THIS IS NOT DONE, ITS THE CONTRACTOR'S FULL RESPONSIBILITY TO COVER ALL COSTS.


41. MECHANICAL CONTRACTOR TO PROVIDE STAMPED AND SIGNED SEISMIC DRAWINGS AND DETAILS FOR ALL MECHANICAL AND PLUMBING ITEMS. SUBMIT THESE DRAWINGS TO THE ENGINEER AND TO THE CITY AS A DEFERRED SUBMITTAL.

42. WHERE NON-OCCUPYABLE SPACES ARE TO BE USED FOR ENVIRONMENTAL AIR MOVEMENT, ALL MATERIALS INSTALLED SHALL BE NON-COMBUSTIBLE OR SHALL LISTED AND LABELED AS HAVING A FLAME SPREAD INDEX OF NOT MORE THAN 25 AND A SMOKE DEVELOPED INDEX OF NOT MORE THAN 50 WHEN TESTED IN ACCORDANCE WITH ASTM E 84 OR UL 723.

43. ALL BALANCING DAMPERS FOR OUTSIDE AIR SERVING AC UNITS ARE TO BE AUTOFLOW DAMPERS UNLESS OTHERWISE NOTED ON THE DRAWINGS. AUTO FLOW DAMPERS ARE TO BE UNITED ENERTECH MODEL CR OR EQUAL.

44. VFD'S AND LINE REACTORS TO BE PROVIDED BY MECHANICAL. INSTALLED AND WIRED BY ELECTRICAL.

HVAC SYMBOLS



LINETYPE LEGEND

— EXISTING - - - DEMOLISHED

— NEW - - - TEMPORARY

- - - FUTURE

DIFFERENT LINETYPE AND SYMBOLS ARE USED THROUGHOUT DRAWINGS TO INDICATE THE CONSTRUCTION PHASE. THE STATUS OF ELEMENTS AND THE CONSTRUCTION PHASE ARE DETERMINED BY THE LINE TYPE IN WHICH THEY APPEAR, AND IS NOT INTENDED TO FULLY DESCRIBE ALL NECESSARY CONSTRUCTION PHASING. THESE DOCUMENTS ARE GENERAL AND ONLY INTENDED TO INDICATE A BROAD ORDER FOR THE SAK OF DESIGNING THE PROJECT. IF THERE IS A DISCREPANCY, CONTRACTOR IS TO CONTACT THE ARCHITECT AND/OR MECHANICAL ENGINEER. THE EXISTING DOCUMENTS ARE AVAILABLE THROUGH THE ARCHITECT.

HATCHING LEGEND

ENLARGED PLAN

NOT IN SCOPE (NIS)

DUCTWORK LINETYPES (LINETYPES ARE IN COLOR)

SA SUPPLY AIR
OA OUTSIDE AIR (VENTILATION)
RA RETURN AIR
TA TRANSFER AIR
EXH GENERAL EXHAUST
G.EXH GREASE EXHAUST
G.EXHF GREASE EXHAUST FUTURE
DV DRYER VENT
FLUE GASEOUS COMBUSTION PRODUCT
CA COMBUSTION AIR

HVAC CONTROL DEVICES

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER


(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER


(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H) HUMIDISTAT (MOUNTED AT 48" A.F.F. UNO)
(TS) TEMPERATURE SENSOR
(SP) STATIC PRESSURE
(DP) DIFFERENTIAL PRESSURE SENSOR
(CO) CARBON MONOXIDE SENSOR
(CO2) CARBON DIOXIDE SENSOR
(NO2) NITROGEN DIOXIDE SENSOR
(CP) CONTROL PANEL
(ATC) AUTOMATED TEMPERATURE CONTROL
(TRX) CONTROL TRANSFORMER

(T) THERMOSTAT (MOUNTED AT 48" A.F.F. UNO)
(H)



1 MECHANICAL PLAN
M201 SCALE: 1/4" = 1'-0"



2 MECHANICAL DEMO FLOOR PLAN
M201 SCALE: 1/4" = 1'-0"

MECHANICAL KEY NOTES

1. REMOVE TRUNK LINE ON LEVEL 2 AS SHOWN. REMOVE ALL ASSOCIATED TAPS. REUSE AS MUCH DUCTWORK AS POSSIBLE FOR NEW DESIGN. SEE 1M201 FOR MORE INFORMATION.
2. REMOVE DUCT TAP AS SHOWN. RELOCATE TO NEW LOCATION AS SHOWN IN 1M201.
3. REMOVE RETURN GRILLE IN FLOOR. RELOCATE TO NEW LOCATION SHOWN IN 1M201.
4. CONNECT DUCT TO RISER COMING THROUGH FLOOR AS SHOWN. REUSE EXISTING DUCTWORK AS MUCH AS POSSIBLE.
5. CONNECT TAPS TO EXISTING DUCT AS SHOWN. REUSE EXISTING DIFFUSERS AS MUCH AS POSSIBLE.
6. RETURN DIFFUSERS LOCATED IN FLOOR.

MECHANICAL GENERAL NOTES

A. ALL FIRE SMOKE DAMPERS ARE TO BE 120V AND ARE TO BE CONTROLLED BY FIRE ALARM CONTRACTOR AND INTERLOCKED WITH FIRE SYSTEM. DAMPERS TO BE LISTED TO MEET OR EXCEED THE RATING OF THE WALLS.

B. CONTRACTOR IS TO PROVIDE / INSTALL ALL DUCTWORK AS HIGH UP AS POSSIBLE AND TIGHT TO BOTTOM OF BEAMS / JOISTS.

C. CONTROLS CONTRACTOR TO COORDINATE FINAL LOCATIONS OF ALL T-STATS WITH OWNER / ARCHITECT PRIOR TO ANY INSTALLATION.

D. ALL DUCT ELBOWS ARE TO BE RADIUS ELBOWS WHERE EVER POSSIBLE TO INSTALL. IF SPACE CONSTRAINTS DO NOT ALLOW FOR THEM TO BE INSTALLED, RADIUS HEEL ELBOWS ARE TO BE USED.

E. ALL DUCT TAKE-OFFS ARE TO BE HIGH EFFICIENCY TAKE-OFFS (HETS).

F. CONTRACTOR TO PROVIDE / INSTALL ACCESS PANELS FOR ALL EQUIPMENT, DAMPERS, ETC. LOCATED ABOVE HARD LID CEILINGS AS REQUIRED.



03/12/2025

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL


1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY


133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.: 2023.040.00
GSBS PROJECT NO.:
ISSUED DATE: 07/21/2025


Mechanical Plan




5 HIGH EFFICIENCY DUCT TAKEOFF DETAIL SQUARE
M501 SCALE: 1/8" = 1'-0"




1 TYPICAL FLOOR DRAIN / SINK DETAIL
M501 SCALE: 1/8" = 1'-0"




6 TYPICAL DUCT TAKEOFF DETAIL
M501 SCALE: 1/8" = 1'-0"




2 DIFFUSER MOUNTING DETAIL (SQUARE)
M501 SCALE: 1/8" = 1'-0"



7 CLEANOUT DETAIL
M501 SCALE: 1/8" = 1'-0"



3 TYPICAL WASTE CONNECTIONS
M501 SCALE: 1/8" = 1'-0"



4 HIGH EFFICIENCY DUCT TAKEOFF DETAIL ROUND
M501 SCALE: 1/8" = 1'-0"



03/12/2025

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden UT 84401
OGDEN CITY

133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.: 2023.040.00
GSBS PROJECT NO.: 07/21/2025
ISSUED DATE: 07/21/2025
Mechanical Details

REVISIONS:	



MECHANICAL & ELECTRICAL
CONSULTING ENGINEERS, LLC.
1040 N 2200 WEST | SALT LAKE CITY, UT
T: 801.359.3158 | www.pve-ut.com

Architectural
REGISTERED
Society of
Utah
83150201

03/12/2025

CONSTRUCTION DOCUMENTS

OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401
OGDEN CITY

133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.: 2023.04.00
GSBS PROJECT NO.: 2023.04.00
ISSUED DATE: 07/21/2025

Plumbing Notes & Legends

PROJECT PLUMBING GENERAL NOTES

- ALL PLUMBING SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH THE CURRENT ADOPTED EDITION OF THE BUILDING CODES, FIRE CODES, MECHANICAL CODES AND PLUMBING CODES.
- DRAWINGS AND SPECIFICATIONS ARE COMPLIMENTARY. THE MOST STRINGENT WILL WHATEVER IS CALLED FOR IN EITHER IS BINDING AS THOUGH CALLED FOR IN BOTH.
- THE EQUIPMENT SPECIFIED ON THE DRAWINGS HAVE BEEN SELECTED AS THE BASIS OF DESIGN. THE USE OF REVIEWED OR APPROVED EQUALS SHALL BE COORDINATED BY THE CONTRACTOR FOR GENERAL CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND GENERAL CONTRACTOR SHALL COORDINATE THE CONTRACTOR FOR THE SELECTION OF EQUIPMENT THAT IS EQUIVALENT IN SIZE, EQUIPMENT DIMENSIONS, AND PERFORMANCE WHICH SHALL BE CONFIRMED AND CORRELATED AT THE JOB SITE. FABRICATION PROCESSES AND TECHNIQUES OF CONSTRUCTION COORDINATION OF HIS WORK WITH THAT OF ALL OTHER TRADES AND THE SATISFACTORY PERFORMANCE OF HIS WORK.
- DRAWINGS ARE DIAGRAMMATIC AND SHOW THE GENERAL DESIGN INTENT, ARRANGEMENT, AND GENERAL EXTENT OF SYSTEMS. DO NOT SCALE DRAWINGS NOR USE AS SHOP DRAWINGS. NEW MECHANICAL EQUIPMENT, DUCTWORK AND PIPING ARE SHOWN AT APPROXIMATE LOCATIONS. THIS CONTRACTOR SHALL FIELD MEASURE/VERIFY ALL MECHANICAL/PLUMBING ITEMS PRIOR TO STARTING NEW WORK AND MAKE ADJUSTMENTS AS REQUIRED. THE CONTRACTOR SHALL NOT MAKE CHANGES TO THE DRAWINGS UNLESS APPROVED BY THE ARCHITECT/ENGINEER. ANY REQUIREMENTS THAT MAY NOT BE SPECIFICALLY CALLED OUT IN THIS PORTION OF THE CONSTRUCTION DOCUMENTS, NOTIFY THE ARCHITECT OR CONTRACTOR.
- VERIFY THAT FINAL EQUIPMENT LOCATIONS MEET MANUFACTURER'S RECOMMENDATIONS REGARDING SERVICE CLEARANCE AND PROPER AIRFLOW CLEARANCE AROUND EQUIPMENT. WHERE ALTERNATIVE ROUTING, OFFSETS, AND TRANSITIONS ARE REQUIRED FOR FIELD COORDINATION OF ALL OTHER TRADES, THIS CONTRACTOR SHALL FIELD COORDINATE WITH ALL OTHER TRADES, AND SHALL MAKE CHANGES WITHOUT ADDITIONAL COSTS.
- PROVIDE TEMPORARY BARRIERS TO CONTAIN DUST AND DEBRIS RESULTING FROM THE PERFORMANCE OF THE WORK TO THE AREA WHERE WORK IS BEING PERFORMED.
- THIS CONTRACTOR SHALL PROVIDE SUBMITTALS ON ITEMS LISTED IN EQUIPMENT SCHEDULE & SPECIFICATIONS TO THE ENGINEER FOR REVIEW PRIOR TO THE ORDER, PURCHASE OR INSTALLATION.
- M.C. & P.C. TO PROVIDE A CONSTRUCTION RECORD SET OF "AS-BUILT" DOCUMENTS TO THE ARCHITECT/ENGINEER REFLECTING ANY VARIANCES OF INSTALLED PIPING LOCATIONS OR EQUIPMENT CONTRARY TO THE CONSTRUCTION DOCUMENTS WITHIN 60 DAYS OF SUBSTANTIAL COMPLETION.
- ALL FLOW RATES, PRESSURES, AND TEMPERATURES MUST BE BALANCED TO THE VALUES INDICATED ON THE FLOOR PLANS. PROVIDE A FINAL BALANCE REPORT FOR THE TESTING AND ADJUSTING OF ALL NEW SYSTEMS SHALL BE COMPLETED PRIOR TO THE FINAL APPROVAL BY THE FIELD INSPECTOR. THIS REPORT SHALL BE SIGNED BY THE INDIVIDUAL RESPONSIBLE FOR PERFORMING THESE SERVICES. T.A.B. CONTRACTOR BY GENERAL CONTRACTOR.

1. ALL METAL PIPE FITTINGS AND PARTS OF FIXTURES BURIED IN THE GROUND SHALL BE PROTECTED BY AT LEAST 1/2 IN. PLASTIC SLEEVES OR EQUIVALENT. EXPOSED FERRULES, PIPING IS PROTECTED UNDERNEATH.
2. ALL METAL PIPE CLAMPS SHALL BE ALLOWED IN THE FIELD WITHOUT INSTALLING UNSTRUT CLAMPS SPECIFICALLY DESIGNED FOR USE IN PIPES.
3. PLASTIC PIPING IN RETURN AIR PLUMIN CEILINGS SHALL BE FIREPROOFED.

PIPING MATERIALS

SYSTEM	LOCATION	MATERIAL
DOMESTIC COLD WATER	BELLOW GROUND	PE, ASTM-D3035
DOMESTIC COLD WATER	ABOVE GROUND	TYPE 'L' COPPER, PEX, CPVC
DOMESTIC HOT WATER	ABOVE GROUND	TYPE 'L' COPPER, PEX
CONDENSATE	IN RETURN AIR PLUMIN	DWV COPPER, TYPE 'M' COPPER
CONDENSATE	NOT IN RETRN AIR PLUMIN	PVC, PE, OR PP PIPE/TUPING
CONDENSATE	AT FCU CONNECTION	1" PVC-TO-COPPER PUSH ADAPTER (SHARKBITE, OR EQUAL)
WASTE & VENT	BELOW GRND & PRR GARAGE	SOLID CORE SCH. 40 PVC
WASTE & VENT	ABOVE GRADE	CAST IRON, ABS DWV PIPING???
ROOF & OVERFLOW DRAIN	BELLOW GROUND	SOLID CORE SCH. 40 PVC
ROOF ..	ABOVE GRADE	CAST IRON, ABS DWV PIPING???

1) ALL METAL PIPE FITTINGS AND PARTS OF FIXTURES BURIED IN THE GROUND SHALL BE PROTECTED BY AT LEAST 1/2 IN. PLASTIC SLEEVES OR EQUIVALENT. EXPOSED FERRULES, PIPING IS PROTECTED UNDERNEATH.

2) ALL METAL PIPE CLAMPS SHALL BE ALLOWED IN THE FIELD WITHOUT INSTALLING UNSTRUT CLAMPS SPECIFICALLY DESIGNED FOR USE IN PIPES.

3) PLASTIC PIPING IN RETURN AIR PLUMIN CEILINGS SHALL BE FIREPROOFED.

PIPE INSULATION TABLE

A. DOMESTIC HOT WATER PIPING (W/ OPERATING TEMP. BETWEEN 105F-140F)						
• 1" THICK FOR PIPE SIZES < 1/2"						
• 1/2" THICK FOR PIPE SIZES 1/2" AND LARGER						
• IN UNCONDITIONED SPACE: 2" THICK FOR PIPE SIZES 1/2" TO 6" & HEAT TRACED W/ MAX 5 WATTS/FT.						
B. DOMESTIC COLD WATER PIPING						
• 1/2" THICK FOR ALL PIPE SIZES 1/2" (WHERE CONDENSATION CONCERN)						
• IN UNCONDITIONED SPACE: 2" THICK FOR PIPE SIZES 1/2" TO 6" & HEAT TRACED W/ MAX 5 WATTS/FT. (PROVIDE CONTINUOUS VAPOR BARRIER.)						

INSULATE PIPING WITH FIBERGLASS PIPE COVERING WITH ALL SERVICE JACKET AND SELF-SEAL. FITTINGS SHALL BE MITERED PIPING COVERING OF GLASS FIBER MOLED FITTINGS FOR USE IN A RETURN AIR PLUMIN CEILINGS. THE CONDUCTIVITY SHALL BE A MAXIMUM OF 0.23 W/M-K THICKNESS AT 75F. ALL EXPOSED PIPING IS TO BE INSULATED AND WEATHERPROOFED. ALL EXPOSED PIPING IS TO BE INSULATED AND WEATHERPROOFED.

Minimum Pipe Insulation Thickness

Fluid Operating Temp. Range & Usage (°F)	Insulation Conductivity	Nominal Pipe or Tube Size (inch)	< 1	1 to < 1 1/2	1 1/2 to < 4	4 to < 8	> 8
>350	0.32-0.34	250	4.5	5.0	5.0	5.0	5.0
251-350	0.29-0.32	200	3.0	4.0	4.5	4.5	4.5
201-250	0.27-0.30	150	2.5	3.5	4.0	4.0	4.0
144-200	0.25-0.28	100	2.0	3.0	3.5	3.5	3.5
105-140	0.21-0.28	100	1.0	1.0	1.5	1.5	1.5
40-60	0.21-0.27	75	0.5	0.5	1.0	1.0	1.0
< 40	0.20-0.269	50	0.5	1.0	1.0	1.0	1.0

INSULATION EXPOSED TO THE WEATHER SHALL BE PROTECTED FROM DAMAGE, INCLUDING THAT CAUSED BY SUNLIGHT, MOISTURE, EQUIPMENT MANUFACTURER'S RECOMMENDED INSULATION, AND ULTRAVIOLET SOLAR RADIATION THAT CAN CAUSE DEGRADATION OF THE MATERIAL. ADHESIVE TAPE SHALL NOT BE PERMITTED. (FOR REFRIGERANT PIPING USE ARMAFLEX SHIELD OR EQUAL)

DHW DISTANCE FROM SOURCE

DHW LOOP IS TO BE ROUTED SUCH THAT THE MAXIMUM ALLOWABLE PIPE LENGTH FROM THE NEAREST SOURCE TO THE TERMINATION OF THE FIXTURE SUPPLY BE IN ACCORDANCE WITH 2018 IFC C404.5.1. USE MAXIMUM ALLOWABLE PIPE LENGTH METHOD OR MAXIMUM ALLOWABLE PIPE VOLUME METHOD. SEE TABLE ON SHEET M001, OR P001. (ASHRAE 90.1 DHW LOOP MAY BE 10' MAX DISTANCE FROM FIXTURE)

PIPING VOLUME AND MAXIMUM PIPING LENGTHS

Nominal Pipe Size (inches)	VOLUME (liquid ounces per foot length)	MAXIMUM PIPING LENGTH (feet)		
		Public bath faucets	Other fixtures and appliances	
1/4	0.33	6	50	
5/16	0.5	4	50	
3/8	0.75	3	50	
1/2	1.5	2	43	
5/8	2	1	32	
3/4	3	0.5	21	
7/8	4	0.5	16	
1	5	0.5	13	
1-1/4	8	0.5	8	
1-1/2	11	0.5	6	
2	18	0.5	4	

31. DHW LOOP IS TO BE ROUTED SUCH THAT THE MAXIMUM ALLOWABLE PIPE LENGTH FROM THE NEAREST SOURCE TO THE TERMINATION OF THE FIXTURE SUPPLY BE IN ACCORDANCE WITH 2018 IFC C404.5.1. USE MAXIMUM ALLOWABLE PIPE LENGTH METHOD OR MAXIMUM ALLOWABLE PIPE VOLUME METHOD. SEE TABLE ON SHEET M001, OR P001. (ASHRAE 90.1 DHW LOOP MAY BE 10' MAX DISTANCE FROM FIXTURE)

BASIS OF DESIGN

CODES (INCLUDING LOCAL AMENDMENTS)

- 2021 INTERNATIONAL MECHANICAL CODE (IMC)
- 2021 INTERNATIONAL ENERGY CONSERVATION CODE (IECC)
- 2021 INTERNATIONAL BUILDING CODE (IBC)
- 2021 INTERNATIONAL PLUMBING CODE (IPC)

5B CLIMATE ZONE

DESIGN TEMPERATURES

SUMMER: 98.3°F DB / 62.6°F WB (OUTDOORS-COOLING)
75°F DB / 50% RH (INDOORS)
WINTER: 8.0°F DB (OUTDOORS - HEATING)
70°F DB (INDOORS)

ELEVATION: 4239 FEET ABOVE SEA LEVEL

POTABLE WATER DISINFECTION

2018 IPC 610 EXCERPT



NEW / REPAIRED POTABLE WATER SYSTEMS SHALL BE DISINFECTED PRIOR TO USE.

- THE PLUMBING SYSTEM SHALL BE FLUSHED WITH CLEAN, POTABLE WATER UNTIL DIRTY WATER DOES NOT APPEAR AT THE POINTS OF OUTLET.
- THE SYSTEM SHALL BE FILLED WITH WATER / CHLORINE SOLUTION CONTAINING NO LESS THAN 200 P.P.M. OF CHLORINE, AND THE SYSTEM SHALL BE VALVED OFF AND ALLOWED TO STAND FOR 3 HOURS.
- FOLLOWING STAND TIME, THE SYSTEM SHALL BE FLUSHED WITH CLEAN, POTABLE WATER UNTIL CHLORINE IS PURGED FROM THE SYSTEM.
- THIS PROCEDURE SHALL BE REPEATED WHERE SHOWN BY A BACTERIOLOGICAL EXAMINATION THAT CONTAMINATION REMAINS PRESENT IN THE SYSTEM.
- PROVIDE TEST / FLUSH DOCUMENTATION TO ARCHITECT W/ BALANCE REPORT, P.C. TO COORDINATE TESTING PROCEDURE WITH PROJECT MANAGER.


PLUMBING SYMBOLS

INDICATES POINT OF CONNECTION OF NEW TO EXISTING MECHANICAL EQUIPMENT, PIPING OR DUCTWORK.
PLAN NOTE CALLOUT
DETAIL REFERENCE: UPPER # INDICATES DETAIL # & LOWER # INDICATES SHEET #.
SECTION CUT DESIGNATION. UPPER # INDICATES VIEW # & LOWER # INDICATES SHEET #.
MECHANICAL EQUIPMENT DESIGNATION. REFER TO MECHANICAL SCHEDULES.
PLUMBING FIXTURE DESIGNATION. REFER TO PLUMBING FIXTURE SCHEDULE.

PIPE SIZE IN



1 PLUMBING FLOOR PLAN
P201 SCALE: 1/4" = 1'-0"



2 PLUMBING DEMOLITION PLAN
P201 SCALE: 1/4" = 1'-0"

PLUMBING GENERAL NOTES

- A. ALL WASTE PIPING LESS THAN 3" DIAMETER TO BE SLOPED AT 1/4" PER FOOT. ALL WASTE PIPING 3" AND GREATER TO BE SLOPED AT 1/8" PER FOOT.
- B. ALL FLOOR DRAINS AND FLOOR SINKS ARE TO HAVE TRAP PRIMERS, OR TRAP GUARDS INSTALLED.
- C. INSTALL WASTE & VENT RISERS AS CLOSE AS POSSIBLE TO COLUMNS.
- D. ALL PLUMBING SHOWN IS BASED ON FIELD OBSERVATIONS. P.C. TO VERIFY ALL SITE CONDITIONS BEFORE STARTING WORK.

PLUMBING KEY NOTES

- 1. REMOVE EXISTING BREAK ROOM SINK AND ALL ASSOCIATED PLUMBING CONNECTIONS. RESUE PLUMBING STUB OUTS FOR NEW LOCATION. SEE 1/201 FOR MORE INFORMATION.
- 2. CONNECT DCW/DHW TO EXISTING LINE.
- 3. CONNECT SANITARY SEWER TO EXISTING LINE.
- 4. ROUTE 1/2" DCW/DHW TO BREAK ROOM SINK. PROVIDE ISOLATION VALVE AND ALL FINAL CONNECTIONS.
- 5. ROUTE 1/2" DCW TO ICE MAKER BOX. PROVIDE ISOLATION VALVE AND ALL FINAL CONNECTIONS.



03/12/2025

CONSTRUCTION DOCUMENTS

OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY

133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.: 2023.040.00
GSBS PROJECT NO.: 07/21/2025
ISSUED DATE: 07/21/2025

Plumbing Plan

LIGHTING SYMBOLS

WIRING DEVICE SYMBOLS

GENERAL SYMBOLS

ELECTRICAL SYMBOL SCHEDULE GENERAL NOTES

ABBREVIATION SCHEDULE


SHEET INDEX

GENERAL PROJECT NOTES:

VIDEO SURVEILLANCE SYMBOLS

BRANCH CIRCUITING SYMBOLS

VOLTAGE DROP UPSIZING CHART FOR 20AMP, SINGLE PHASE BRANCH CIRCUITS



KEYED NOTES


P1. PROTECT AND MAINTAIN

CONSTRUCTION DOCUMENTS

OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY




8 TYPICAL LAY-IN GRID LIGHT FIXTURE MOUNTING DETAIL
SCALE: NTS

ANCHOR TO CONCRETE CEILING USING 3/4" PIN & ANGLE CLIP (TYP.)
#12 STEEL WIRE (TYP.)
LAY-IN TILE CEILING
ANCHOR TO CONCRETE CEILING
LAY-IN TROFFER
ACOUSTICAL T-BAR SEISMIC CLIP (CADDY S15 OR S15A TO SUIT APPLICATION OR EQUIVALENT) PROVIDE 4 CLIPS PER FIXTURE

2' x 4' OR 1' x 4'
2' x 2'

SUPPORT CLIP ARRANGEMENT DIAGRAMS




5 TYPICAL CONCRETE WALL PENETRATION DETAIL
SCALE: NTS

DAMMING MATERIAL (BACKER ROD, FIBER-GLASS OR MINERAL WOOL)
FIRE RATED CONCRETE WALL (SOLID OR BLOCK)
METAL PIPE OR CONDUIT
CP 28HB CAULK ON BOTH SIDES OF WALL


1/4" MINIMUM DIAMETER BEAD OF 3M FIRE BARRIER CP 25 CAULK OR MP MOLDABLE PUTTY

NOTE:
1. TYPICAL DETAILS SHOWING GENERAL FIRE STOPPING PROCEDURE. ACTUAL PROCEDURE DEPENDS UPON ANNUAL SPACE BETWEEN PIPE AND/OR INSULATION AND OPENING. FOLLOW MANUFACTURER'S INSTRUCTIONS.
2. FIRESTOP TESTED UP TO 4 HOURS IN ACCORDANCE WITH ASTM E 814 (UL 1475) & CANULC S15.



4 TYPICAL GYPSUM BOARD WALL PENETRATION DETAIL
SCALE: NTS

STEEL STUD
GYPSUM BOARD
SOUND ATTENUATION INSULATION (STC WALLS)
METALLIC CONDUIT
1/4" MINIMUM DIAMETER BEAD OF 3M FIRE BARRIER CP 25 CAULK OR MP MOLDABLE PUTTY




3 TYPICAL ADA AND EQUIPMENT MOUNTING HEIGHT DETAIL
SCALE: NTS

NOTES:
1. MOUNT ALL OUTLETS, DEVICES, AND EQUIPMENT AT HEIGHTS INDICATED BELOW, UNLESS NOTED OTHERWISE ON THE DRAWINGS. UNLESS NOTED OTHERWISE, HEIGHTS ARE GIVEN FROM FINISHED FLOOR TO CENTER OF OUTLET BOX.
2. WHERE OUTLETS, DEVICES AND EQUIPMENT ARE NOTED BY THE SUBSCRIPT 'A', MOUNT AT 4" ABOVE COUNTER. IF COUNTER HAS A BACK SPLASH, MOUNT AT 4" ABOVE BACK SPLASH. REFER TO ARCHITECTURAL INTERIOR ELEVATIONS AND COORDINATE WITH CASEWORK SUPPLIER.

DISCONNECT SWITCH (TYP.)
ELECTRICAL PANELBOARD, FAFC PANEL AND SECURITY PANEL
COUNTERTOP WITH BACKSPLASH
COUNTERTOP ONLY
DATA PHONE AND ELECTRICAL OUTLETS
CASEWORK: BY OTHERS
72" MAX TO TOP
48-72" TO TOP

STRUCTURAL JOIST OR BEAM
DECK
Lay-in or Hard Lid Ceiling
FIRE ALARM BEAM DETECTOR
FIRE ALARM STROBE AND HORN/STROBE
FIRE ALARM AND GENERATOR ANNUNCIATOR
ADA PUSH BUTTONS, LIGHTING CONTROLS, FIRE ALARM PULL STATIONS, AND CARD ACCESS
CEILING MOUNTED FIRE ALARM STROBE AND HORN/STROBE
SMOKE AND HEAT DETECTORS
30'-0" MAX
80" BOTTOM MIN 96" TOP MAX (MEASURED FROM LENS)
48" MAX
60"
18" MIN.

ADA ACCESSIBILITY CHART



1 TYPICAL ROUGH-IN REQUIREMENTS
SCALE: NTS

NOTES:
1. TYPICAL FOR WOOD AND METAL STUD ROUGH-IN.
2. PLASTER RINGS NOT SHOWN.
3. LOCATE ALL OUTLET BOXES IN ACCORDANCE WITH ARCHITECTURAL AND MECHANICAL DRAWINGS, AND WITH ALL APPLICABLE SHOP DRAWINGS.
4. OUTLETS ON OPPOSITE SIDES OF FIRE-RATED WALLS OR PARTITIONS IN THE SAME STUD SPACE MUST BE SEPARATED BY A MINIMUM OF 24" HORIZONTAL DISTANCE.

TYPICAL WALL OUTLET
BAR STRAPS
PROVIDE CONDUIT SUPPORTS IN ACCORDANCE WITH NEC AND SPECIFICATION SPACING REQUIREMENTS FOR TYPE OF RACEWAY REQUIRED
AS REQUIRED FOR TYPE OF CONSTRUCTION
BOX SUPPORT
TYPICAL OUTLET BOX
TYPICAL S OUTLET BOX
BAR STRAPS
PLASTER RINGS NOT SHOWN
DESIGNATION OF CIRCUIT, WIRE COMPLETE
ISOLATED GROUND CIRCUIT

CONSTRUCTION DOCUMENTS
OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401
OGDEN CITY

133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.: 2023.04.00
GSBS PROJECT NO.: 2023.04.00
ISSUED DATE: 07-21-2025

ELECTRICAL DETAILS

EG002 | REV

Light Fixture Schedule							
Type	Description	Source	Electrical		Approved Manufacturers	Catalog Information Catalog Number / Series	Comments / Notes
			Voltage	Load			
G1	DESCRIPTION: LED 2x4 DIMENSION: 3.25"H x 23.75"W x 47.75"L MOUNTING: RECESSED IN LAY-IN CEILING MATERIAL: ROLLED STEEL, FINISH: WHITE LENS MATERIAL: ACRYLIC LENS REFLECTOR DISTRIBUTION TYPE: TBD	LAMP TYPE: LED LUMENS: 4000 DIMMING: 0-10V COLOR TEMP: 4000K	120 V	30	METALUX (OR APPROVED EQUAL)	24CZ2-40-UNV-L840-CD1-U	-
PL3	DESCRIPTION: LED LINEAR PENDANT DIMENSION: 8.5"x48" MOUNTING: PENDANT MATERIAL: STEEL, FINISH: WHITE LENS MATERIAL: FROSTED ACRYLIC PROVIDE WITH EMERGENCY BATTERY PACK WHERE INDICATED ON FLOOR PLANS	LAMP TYPE: LED LUMENS: 3000 DIMMING: 0-10V COLOR TEMP: 4000K	120 V	26	CORELITE (OR APPROVED EQUAL)	J2-WL-30L840-1D-UNV-STD-DC-W-AC120-UM	PROVIDE WITH EMERGENCY BATTERY PACK WHERE INDICATED ON FLOOR PLANS
PL4	DIMENSION: 8.5"x48" MOUNTING: PENDANT MATERIAL: STEEL, FINISH: WHITE LENS MATERIAL: FROSTED ACRYLIC PROVIDE WITH EMERGENCY BATTERY PACK WHERE INDICATED ON FLOOR PLANS	LAMP TYPE: LED LUMENS: 4000 DIMMING: 0-10V COLOR TEMP: 4000K	120 V	37	CORELITE (OR APPROVED EQUAL)	J2-WL-40L840-1D-UNV-STD-DC-W-AC120-UM	PROVIDE WITH EMERGENCY BATTERY PACK WHERE INDICATED ON FLOOR PLANS
X1	DESCRIPTION: LED EXIT SIGN DIMENSION: 13" x 2-1/8" x 4-1/2" MOUNTING: WALL MATERIAL: POLYCARBONATE, COLOR: TBD LENS MATERIAL: N/A LENS REFLECTOR DISTRIBUTION TYPE: N/A	LAMP TYPE: LED LUMENS: N/A DIMMING: N/A COLOR TEMP: N/A	120 V	2	SURE LITES (OR APPROVED EQUAL)	APX7RG	-

LIGHT FIXTURE GENERAL NOTES

1. REFER TO THE ARCHITECTURAL REFLECTED CEILING PLANS FOR LOCATIONS OF LIGHT FIXTURES. BRING ALL DISCREPANCIES OF LOCATIONS AND QUANTITIES TO THE ATTENTION OF THE ARCHITECT PRIOR TO BIDDING.
2. CONFIRM MOUNTING HEIGHTS AND LOCATIONS OF ALL LIGHT FIXTURES WITH ARCHITECTURAL ELEVATIONS AND / OR ARCHITECT.
3. REFER TO THE SPECIFICATIONS FOR OTHER LIGHT FIXTURE REQUIREMENTS.
4. CONFIRM AVAILABLE MOUNTING DEPTHS OF ALL LIGHT FIXTURES AND COMPARE WITH DEPTHS SHOWN ON SHOP DRAWINGS. BRING ALL POTENTIAL CONFLICT AREAS TO THE ATTENTION OF THE ARCHITECT AND ELECTRICAL ENGINEER PRIOR TO RELEASE.
5. ALL LIGHT FIXTURES ARE TO BE 3500K FOR INTERIOR APPLICATIONS AND 4000K FOR EXTERIOR APPLICATIONS, UNLESS OTHERWISE NOTED IN THE FIXTURE DESCRIPTION.
6. ALL LIGHT FIXTURES ARE TO BE A MINIMUM OF 80 CRI UNLESS OTHERWISE NOTED IN THE FIXTURE DESCRIPTION.
7. ALL LED SOURCES MUST MEET L80 AT 50,000 HRS MINIMUM UNLESS OTHERWISE NOTED.
8. CONFIRM ALL MOUNTING REQUIREMENTS WITH ARCHITECT PRIOR TO RELEASE.
9. ALL LIGHT FIXTURES ARE TO HAVE AN EFFICACY OF 80 LUMENS PER WATT MINIMUM.

BIDDING REQUIREMENTS

1. BID ONLY PRODUCTS THAT ARE SPECIFIED OR APPROVED BY ADDENDUM.
2. PACKAGING OF LIGHT FIXTURES WITH OTHER SYSTEMS IS NOT ALLOWED AND MUST BE BID SEPARATELY. I.E. LIGHT FIXTURES, THEATRICAL LIGHTING, SPORTS LIGHTING AND ALL LIGHTING CONTROLS.
3. WHEN ONLY ONE PRODUCT IS APPROVED FOR BIDDING, THE PRICE FOR THAT ITEM SHALL BE BROKEN OUT SEPARATELY WHEN SUBMITTING PRICING TO VARIOUS DISTRIBUTORS AND / OR CONTRACTOR.
4. WHEN A CONTRADICTION EXISTS BETWEEN A SPECIFIC MODEL NUMBER AND THE DESCRIPTION, THE DESCRIPTION SHALL GOVERN.

LIGHT FIXTURE PRIOR APPROVAL REQUIREMENTS

1. PRIOR APPROVAL IS REQUIRED BEFORE BIDDING THIS PROJECT.
2. PRIOR APPROVALS SHALL BE SUBMITTED TO THE ELECTRICAL ENGINEER'S OFFICE AT LEAST (8) WORKING DAYS BEFORE BID TIME. PRIOR APPROVALS RECEIVED AFTER THIS TIME PERIOD SHALL BE REJECTED.
3. ITEMS THAT ARE SUBMITTED AND HAVE BEEN APPROVED WILL BE LISTED IN THE ADDENDUM(S). VERBAL APPROVALS WILL NOT BE GIVEN ON ANY ITEM.
4. IT IS NOT THE RESPONSIBILITY OF THE ELECTRICAL ENGINEER TO NOTIFY THE SUBMITTING PARTY OF ERRORS IN THE SUBMITTAL. NOTIFICATION OF ERRORS BY THE ELECTRICAL ENGINEER PRIOR TO ISSUANCE OF THE ADDENDUM(S) MAY NOT BE GIVEN.
5. PRIOR APPROVALS SHALL CONSIST OF CUT SHEETS DESCRIBING THE PRODUCTS BEING SUBMITTED AS EQUIVALENTS. ALL SPECIFICATION INFORMATION SHALL BE CLEARLY MARKED. PRODUCTS WITHOUT PHOTOMETRIC DATA WILL NOT BE APPROVED.
6. LIGHTING PACKAGES WILL BE REVIEWED FOR GENERAL PROJECT COMPLIANCE ONLY. AN IN-DEPTH REVIEW OF ANY ALTERNATE FIXTURES WILL BE DONE DURING THE SUBMITTAL REVIEW PROCESS. ANY FIXTURES THAT ARE NOT TRULY EQUAL, AND / OR DO NOT COMPLY WITH ALL OF THE REQUIREMENTS CONTAINED IN THE CONTRACT DOCUMENTS, WILL NOT BE APPROVED. IF EQUIPMENT IS DISAPPROVED FOR BIDDING, CONTRACTOR SHALL SUPPLY SPECIFIED EQUIPMENT AT NO EXTRA COST TO THE OWNER.

PANELBOARD SCHEDULE

Panel Name: B										Location:				Feed From:			
Mounting: Surface				Voltage: 120/208 Wye				Main Type: MCB				SPD:					
Enclosure: NEMA 1				Phase: 3				Bus Rating: 225 A				Neutral Rating:					
Door Type: Standard				Wires: 4				MCB Rating: 150 A				Isolated Ground:					
Manufacturer: GE (Existing)				Min. A.I.C. Rating: 10,000 A				Bus Material: Copper									
Branch Breakers																	
Keyed Note	Circuit Description	AMP	Pole	Load Type	Ckt #	A		B		C		Ckt #	Load Type	Pole	AMP	Circuit Description	Keyed Note
8	REC: CEMETARY OFFICE	20 A	1	CO	1	900 VA	--					2	--	1	--	EXISTING SPACE	
8	REC: BREAK ROOM OUTLETS	20 A	1	CO	3			360 VA	--			4	--	1	--	EXISTING SPACE	
8	BREAK ROOM MICROWAVE	20 A	1	K	5					1500 VA	--	6	--	1	--	EXISTING SPACE	
1,8	BREAK ROOM FRIDGE	20 A	1	K	7	1200 VA	--					8	--	1	--	EXISTING SPACE	
8	BREAK ROOM DISPOSAL	20 A	1	M; E	9			1200 VA	--			10	--	1	--	EXISTING SPACE	
8	REC: NEW OFFICE 105, 106	20 A	1	CO	11					540 VA	--	12	--	1	--	EXISTING SPACE	
	EXISTING SPACE	--	1	--	13	--	--					14	--	1	--	EXISTING SPACE	
	EXISTING SPACE	--	1	--	15			--	--			16	--	1	--	EXISTING SPACE	
	EXISTING SPACE	--	1	--	17					--	0 VA	18	--	2	100 A	EXISTING LOAD	9
9	EXISTING LOAD	20 A	1	--	19	0 VA	0 VA					20	--	--	--	--	--
9	EXISTING LOAD	20 A	1	--	21			0 VA	0 VA			22	--	1	20 A	EXISTING LOAD	9
9	EXISTING LOAD	20 A	1	--	23					0 VA	0 VA	24	--	1	20 A	EXISTING LOAD	9
9	EXISTING LOAD	20 A	1	--	25	0 VA	0 VA					26	--	1	20 A	EXISTING LOAD	9
9	EXISTING LOAD	20 A	1	--	27			0 VA	0 VA			28	--	1	20 A	EXISTING LOAD	9
	EXISTING SPACE	--	1	--	29					--	0 VA	30	--	1	20 A	EXISTING LOAD	9
TOTAL CONNECTED LOAD PER PHASE (VA)						2100 VA		1560 VA		2040 VA							
TOTAL CONNECTED CURRENT PER PHASE (AMPS)						18 A		13 A		18 A							
Panel Totals:																	
TOTAL CONNECTED LOAD:						5700 VA						TOTAL CONNECTED CURRENT:					
TOTAL ESTIMATED DEMAND:						6000 VA						TOTAL ESTIMATED DEMAND CURRENT:					

PANEL BOARD SCHEDULE KEYED NOTE:

PANELBOARD SCHEDULE RATED NOTE:

1. PROVIDE CLASS A GROUND FAULT INTERRUPTER TYPE CIRCUIT BREAKER.
2. PROVIDE ARC FAULT CIRCUIT INTERRUPTER TYPE CIRCUIT BREAKER.
3. PROVIDE 30 MILLIAMPERE EQUIPMENT GROUND FAULT PROTECTOR TYPE CIRCUIT BREAKER.
4. PROVIDE SHUNT TRIP CIRCUIT BREAKER WITH 120 V COIL.
5. PROVIDE HACR RATED CIRCUIT BREAKER.
6. PROVIDE HANDLE CLAMP FOR HOLDING CIRCUIT BREAKER IN THE "ON" OR "OFF" POSITION.
7. PROVIDE SWITCHING RATED CIRCUIT BREAKER.
8. PROVIDE NEW CIRCUIT BREAKER IN EXISTING PANELBOARD (WHERE PANEL IS LABELED AS EXISTING) OF SAME MANUFACTURER AND A.I.C. RATING AS EXISTING.
9. EXISTING LOAD.

CONSTRUCTION DOCUMENTS

OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY

133 W 29th Street, Ogden, UT 84401

OWNER PROJECT NO.:
GSBS PROJECT NO.: 2023.040.
ISSUED DATE: 07-21-2023

REV

LIGHTING WIRING DIAGRAMS			
SYMBOL	DESCRIPTION	MOUNTING	REMARKS
	LINE VOLTAGE LIGHT SWITCH	+48"	
	LINE VOLTAGE LIGHT SWITCH	+48"	
	LOW VOLTAGE LIGHT SWITCH (REFER TO LOW VOLTAGE LIGHTING CONTROL WALL SWITCH DETAILS AND FLOOR PLANS)	+48"	
	WALL MOUNT GRAPHIC TOUCH PAD CONTROLLER	+48"	
	OCCUPANCY SENSOR	CEILING	
	DAYLIGHT SENSOR	CEILING	
	NORMAL POWER LIGHTING LOAD	CEILING	*a LOWER CASE LETTER SPECIFIES ZONE
	EMERGENCY POWER LIGHTING LOAD	CEILING	*a LOWER CASE LETTER SPECIFIES ZONE
	RP: RELAY PACK RPD: DIMMING RELAY PACK RC: RECEPTACLE LOAD CONTROLLER	ABOVE ACCESSIBLE CEILING	RELAYS MAY BE COMBINED IN ROOM CONTROLLER OR POWER PACKS.
	ER: EMERGENCY RELAY PACK ERD: EMERGENCY DIMMING RELAY PACK	ABOVE ACCESSIBLE CEILING	RELAYS MAY BE COMBINED IN ROOM CONTROLLER OR POWER PACKS. MUST BE UL 924 RATED FOR EMERGENCY LOADS.
—	3/4" C WITH LIGHTING BRACH CIRCUIT WIRING		
—	3/4" C WITH 0-10V DIMMING WIRING		
—	3/4" C WITH CAT 5 CABLING		

LIGHTING CONTROL NOTES

1. PROGRAMMING SHALL BE COMPLETED PRIOR TO SUBSTANTIAL COMPLETION.
2. MODIFY PROGRAMMING AND PRESET SCENES AS REQUESTED BY OWNER.
3. PROVIDE FINE TUNING PROGRAMMING MODIFICATIONS AS REQUESTED BY OWNER WITHIN 6 MONTHS AFTER BUILDING OCCUPANCY.
4. IN ADDITION TO PRESET SCENES PROVIDE INDIVIDUAL CONTROL FOR EACH ZONE.
5. ALL WIRING DIAGRAMS ARE GENERAL IN NATURE. SPECIFIC CONFIGURATION AND QUANTITIES DUE TO MANUFACTURER AVAILABILITY WILL VARY. PROVIDE ALL REQUIRED PARTS OF THE SYSTEM TO PERFORM AS INTENDED.
6. NOT ALL DEVICES SHOWN IN WIRING DIAGRAMS MIGHT BE REQUIRED. REFER TO FLOOR PLANS FOR DEVICE QUANTITY AND DEVICE TYPES.
7. PROVIDE SEPARATE RELAYS FOR DAYLIGHT ZONES SHOWN ON DRAWINGS.
8. ROOM CONTROLLERS OR POWER PACKS WITH MULTIPLE RELAYS INCLUDED MAY BE PROVIDED IN LIEU OF SEPARATE RELAYS SHOWN.
9. LIGHTING CONTROL DIAGRAMS AS SHOWN ARE FOR BASIC CONCEPT AND LAYOUT. LIGHTING CONTROLS SYSTEM SUPPLIER TO PROVIDE INSTALLATION DRAWINGS THAT REFLECT THE ACTUAL INSTALLATION REQUIREMENTS, WIRING DIAGRAMS, AND ALL REQUIRED DEVICES.


SYMBOL: \$LV1	SYMBOL: \$LV2	SYMBOL: \$LV3	SYMBOL: \$LV4	SYMBOL: \$LV5
SYMBOL: \$OS	SYMBOL: \$OSD	SYMBOL: \$OS	SYMBOL: \$OS	SYMBOL: \$TIM

LIGHTING CONTROL WALL SWITCH DETAILS

SCALE: NTS


3 LTG.502.STD - LOW VOLTAGE WIRING DIAGRAM

SCALE: NTS





STANDARD SEQUENCE OF OPERATIONS							
ROOM DESIGNATIONS	OCCUPANCY SENSOR	TIME SWITCH			CONTROLS		
		AUTO ON OCCUPANCY	MANUAL ON (VACANCY)	AUTO OFF (TIMEOUT)	AUTO PARTIAL OFF	AUTO OFF AFTER HOURS	TIME ON
LC.BR	BREAKROOM	X	20 MIN				
LC.LO.1	LOBBY (GENERAL)	100%		20 MIN			
LC.PO	PRIVATE OFFICE	X	20 MIN				
LC.RE	RECEPTION STATION	X	20 MIN				

SEQUENCE OF OPERATIONS



4 LTG.503.STD - LOW VOLTAGE WIRING DIAGRAM


SCALE: NTS



1

IV:2024-283

PROFESSIONAL ENGINEER
9808039-2202
ALEKSANDAR
RANKOVIC
State of Utah
07/21/2025



CONSTRUCTION DOCUMENTS

OGDEN COMMUNITY SERVICES BLDG REMODEL

1875 Monroe Blvd, Ogden UT 84401

OGDEN CITY

133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.:
GSBS PROJECT NO.: 2023.040.00
ISSUED DATE: 07-21-2023
LIGHTING PHOTOMETRY PLAN

LIGHTING PHOTOMETRY PLAN

A black and white compass rose with a thick outer circle. The letter 'N' is positioned at the top, above the horizontal line, indicating the North direction.

EL201 | REV

POWER GENERAL NOTES:

- ALL 120V, 20AMP OUTLETS THAT ARE WITHIN 6' OF ANY SINK SHALL BE GFCI.
- THE DIVISION 26 CONTRACTOR SHALL DETERMINE THE EXACT ROUTING OF ALL CONDUIT IN THE FIELD. THIS PLAN REPRESENTS A SCHEMATIC REPRESENTATION OF DEVICE LOCATIONS AND CONDUIT RUNS.
- BOND ALL NEW POWER, TELECOM, AND SECURITY CONDUITS.

KEYED NOTES:

P1 CIRCUIT TO EXISTING GENERAL PURPOSE OUTLETS CIRCUIT IN THIS AREA. EXTEND CONDUIT AND WIRING AS REQUIRED.

P2 PROVIDE 4-11/16" X 4-11/16" X 2-10" BOX WITH SINGLE GANG MUD RING FOR NEW DATAPHONE OUTLET. EXTEND 1" CONDUIT WITH PULLSTRING FROM BOX TO BASEMENT TELECOM EQUIPMENT. COORDINATE ALL WORK WITH THE OWNER PRIOR TO ROUGH-IN.



P3 COORDINATE WORK WITH MILLWORK INSTALLER.

P4 PROVIDE J-BOX FOR SECURITY CAMERA. EXTEND 1" CONDUIT WITH PULLSTRING FROM BOX TO BASEMENT EQUIPMENT RACK. COORDINATE ALL WORK WITH THE OWNER PRIOR TO ROUGH-IN.


REVISIONS:

ENV.2024-283

ENVISION
ENGINEERING
240 E. MORRIS AVE. SUITE 200
SALT LAKE CITY, UT 84115
P (801) 534-1130
www.envisioneng.com



BREAK ROOM 104 EAST WALL - POWER



LEVEL 1 - POWER AND SYSTEMS PLAN

CONSTRUCTION DOCUMENTS
OGDEN
COMMUNITY
SERVICES BLDG
REMODEL

1875 Monroe Blvd, Ogden UT 84401
OGDEN CITY

133 W 29th Street, Ogden, UT 84401
OWNER PROJECT NO.: 2023.04.00
GSBS PROJECT NO.: 07-21-2025
ISSUED DATE: 07-21-2025

**LEVEL 1 - POWER AND
SYSTEMS PLAN**

